

ÖLFLEX® FD 890/890 CY

Super Flexible Heavy Duty Continuous Flex Control Cable with PVC Jacket



ÖLFLEX® FD 890 is a time-tested, performance-proven multi-conductor cable designed for continuous flex applications. Fine stranding and specially formulated compounds optimize flexing life and provide excellent resistance to mineral oils, synthetic oils, and water-based coolants. ÖLFLEX® FD 890 CY is a shielded version available with an overall tinned copper braid. This is recommended when electrical interference needs to be suppressed.

Recommended Applications

Cable tracks & power chains; gantry robots; pick and place units; conveyor systems; machine tool and other continuous flexing applications

Approvals



Cable Attributes		page 640	
OIL	OR-04	FLAME	FR-02
MOTION	CF-03	MECH.	MP-02

Complete the Installation	
SKINTOP® Strain Relief	page 488
EPIC® Connectors	page 280

ÖLFLEX® CONNECT Solution	
ÖLFLEX® CONNECT CHAIN	page 609

Unshielded Construction

Conductors: Finely stranded bare copper

Insulation: Specially formulated PVC; dry lubricant; non-woven wrapping over outer layer

Jacket: Specially formulated PVC; black

Shielded Construction

Conductors: Finely stranded bare copper

Insulation: Specially formulated PVC; dry lubricant; non-woven wrapping over outer layer

Inner Jacket: PVC

Shielding: Tinned copper braid (85% coverage)

Jacket: Specially formulated PVC; black

Application Advantage

- Meets Oil Res I/II, resistant to harsh environments for long service life
- Pressure-extruded jacket for precision connectorization
- Passes UL 1277 impact and crush tests

Technical Data

Minimum Bend Radius:	- for continuous flexing: 7.5 x cable diameter - shielded: 10 x cable diameter	Color Code:	Black with white numbers, plus green/yellow ground
Temperature Range:	- for continuous flexing: -5°C to +90°C - for stationary use: -25°C to +90°C	Approvals:	UL: AWM 2587 AWM 21098 (Oil) Attributes: UL Oil Res I/II Sunlight resistant NFPA 79 UL 758 80°C Oil Test Canada: CSA AWM I/II A/B FT1 CSA C22.2, 210.2 Additional: CE & RoHS
Nominal Voltage:	600V		
Test Voltage:	2000V		
Conductor Stranding:	Better than Class 6 super fine wire		

If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question. For current information go to our website.

ÖLFLEX® FD 890

Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (in) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® Non-Metallic PG Thread	Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (in) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® Non-Metallic PG Thread
20 AWG (0.50 mm²)							14 AWG (2.50 mm²)						
8920034	3	0.264	6.7	10	43	S2109	8914044	4	0.456	11.6	67	148	S2113
8920044	4	0.291	7.4	16	53	S2111	8914074	7	0.614	15.6	117	227	S2121
8920054	5	0.323	8.2	19	68	S2111	12 AWG (4 mm²)						
8920074	7	0.382	9.7	27	75	S2113	8912044	4	0.531	13.5	104	208	S2121
8920124	12	0.457	11.6	39	124	S2113	8912074	7	0.740	18.8	181	335	S2129
8920184	18	0.539	13.7	69	183	S2121	10 AWG (6 mm²)						
8920254	25	0.677	17.2	96	265	S2121	8910044	4	0.640	16.3	155	275	S2121
18 AWG (1.00 mm²)							8 AWG (10 mm²)						
8918034	3	0.287	7.3	18	46	S2111	8908044	4	0.756	19.2	259	481	S2129
8918044	4	0.327	8.3	24	60	S2111	6 AWG (16 mm²)						
8918054	5	0.355	9.0	29	74	S2111	8906044	4	0.909	23.1	413	709	S2129
8918074	7	0.429	10.9	41	102	S2113	4 AWG (25 mm²)						
8918124	12	0.500	12.7	70	158	S2116	8904044	4	1.059	26.9	646	1005	S2136
8918154	15	0.559	14.2	88	202	S2121	2 AWG (35 mm²)						
8918184	18	0.614	15.6	105	234	S2121	8902044	4	1.252	31.8	904	1240	S2248
8918254	25	0.763	19.4	146	336	S2129							
8918344	34	0.826	21.0	211	434	S2129							
16 AWG (1.50 mm²)													
8916034	3	0.323	8.2	30	79	S2111							
8916044	4	0.358	9.1	39	106	S2111							
8916054	5	0.393	10.0	49	132	S2113							
8916074	7	0.480	12.2	68	138	S2116							
8916124	12	0.555	14.1	117	214	S2121							
8916184	18	0.685	17.4	175	323	S2129							
8916254	25	0.854	21.7	242	505	S2129							
8916344	34	0.925	23.5	329	623	S2129							
8916504	50	1.094	27.8	437	880	S2136							

ÖLFLEX® FD 890 CY

Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (in) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® MS-SC PG Thread	Part Number	Number of Conductors (incl. ground)	Nominal Outer Diameter (in) (mm)		Copper Weight (lbs/mft)	Approx. Weight (lbs/mft)	SKINTOP® MS-SC PG Thread
20 AWG (0.50 mm²)							14 AWG (2.50 mm²)						
8920034S	3	0.342	8.7	27	82	53112220	8914044S	4	0.551	14.0	103	181	53112250
8920044S	4	0.370	9.4	38	97	53112230	8914074S	7	0.709	18.0	175	347	53112260
8920054S	5	0.409	10.4	44	108	53112230	8914184S	18	1.012	25.7	385	762	53112270
8920074S	7	0.468	11.9	52	137	53112240	12 AWG (4 mm²)						
8920124S	12	0.551	14.0	68	214	53112250	8912044S	4	0.650	16.5	160	302	53112250
8920184S	18	0.657	16.7	112	293	53112250	8912074S	7	0.858	21.8	251	194	53112260
8920254S	25	0.803	20.4	158	421	53112260	10 AWG (6 mm²)						
18 AWG (1.00 mm²)							8910044S	4	0.752	19.1	215	333	53112260
8918034S	3	0.375	9.5	40	91	53112230	8 AWG (10 mm²)						
8918044S	4	0.419	10.6	48	112	53112230	8908044S	4	0.882	22.4	330	701	53112260
8918054S	5	0.447	11.4	57	131	53112240	6 AWG (16 mm²)						
8918074S	7	0.528	13.4	76	198	53112240	8906044S	4	1.066	27.1	498	986	53112270
8918124S	12	0.636	16.2	125	271	53112250							
8918184S	18	0.719	18.3	162	357	53112260							
8918254S	25	0.887	22.5	218	538	53112260							
8918344S	34	0.986	25.0	211	660	53112270							
16 AWG (1.50 mm²)													
8916034S	3	0.409	10.4	54	121	53112230							
8916044S	4	0.444	11.3	68	154	53112240							
8916054S	5	0.480	12.2	81	170	53112240							
8916074S	7	0.598	15.2	125	258	53112250							
8916124S	12	0.673	17.1	174	366	53112260							
8916184S	18	0.826	21.0	239	493	53112260							
8916254S	25	0.996	25.3	320	687	53112270							
8916344S	34	1.067	27.1	446	769	53112270							

Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section. If not otherwise specified, all values relating to the product are nominal values. For current information go to our website.