

# OLYMPIC WIRE & CABLE CORP.

Toll-Free (800) 526-2269

Ver 4.1.1

## PRODUCT DATA SHEET

**PART NUMBER: 2202L**

*Issued:* Tuesday, April 15, 2003

**CABLE TYPE: LOW VOLTAGE RISER**

### CABLE CONSTRUCTION:

NUMBER OF CONDUCTORS:  
NUMBER OF PAIRS: 1  
GAUGE: 18  
STRANDING: 7

### PERFORMANCE:

DC RESISTANCE: 6.28 OHMS PER MFT AT 20 C  
CAPACITANCE: PF PER FT NOM AT 1 KHZ  
IMPEDENCE: OHMS + - 15% FROM 1-20 MHZ  
NOMINAL VEL OF PROP:

### CONDUCTOR TYPE:

BARE COPPER: X  
TINNED COPPER:  
SILVER PLATED COPPER:  
ALLOY TYPE:  
INSULATION MATERIAL: PVC  
DIELECTRIC OD INCHES:  
INSULATION THICKNESS: .007 INCHES  
COLOR CODE 1: BLACK & RED

### ATTENUATION:

### DB PER 100 FEET:

MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:

NOTES:

COLOR CODE 2:

FILLER:

BARRIER:

SHIELD:

ARMOR:

DRAIN WIRE:

UL STYLE: CL3R, CMR

CSA STYLE:

MILITARY SPEC:

PASS VW1 FLAME TEST: YES VOLTAGE: 300

IEEE -383 TEST:

CE COMPLIANT:

PRINT LEGEND:

RIP CORD:

JACKET MATERIAL: PVC

JACKET THICKNESS: .014 INCHES

JACKET COLOR: GREY

NOMINAL O.D.: .150 INCHES

NEC TYPE: 725, 800

OPERATING TEMPERATURE: 75 C

WEIGHT PER 1000FT: 15 LBS

PUT UPS:

APPROVED BY