

CL3R/CMR Non-shielded 20 AWG & 22 AWG 300V

CL3R/CMR - Nonshielded Conductors
PVC Insulation & Jacket
300 Volt - 22 AWG & 20 AWG



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded bare copper to ASTM B-3, B-8, and B-286

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC) Includes ripcord

Standards:

- NEC Article 725 Type CL3R
- NEC Article 800 Type CMR
- CSA CMG 60C FT-4

Category Insulation Description:

- Color coded Polyvinyl Chloride (PVC)

Applications:

- Power limited control circuits
- Wiring of the following systems: Intercom, Security, & Audio
- Suggested Voltage Rating: 300 Volts

Part Number Table

Part#	Gauge	Conductors	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')	Material Weight (KG/KM)
DS92202	22	2	0.008	0.015	0.122	8.6	12
DS92203	22	3	0.008	0.015	0.129	11	16
DS92204	22	4	0.008	0.015	0.156	15.1	22
DS92206	22	6	0.008	0.015	0.164	20	29
DS92208	22	8	0.008	0.015	0.18	26.2	38
DS92210	22	10	0.008	0.015	0.212	36	53
DS92212	22	12	0.008	0.015	0.219	42	62
DS92002	20	2	0.008	0.015	0.134	11	16
DS92004	20	4	0.008	0.015	0.156	20	29

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC