



## HELUTOP® HT

The plastic cable gland with vibration protection

### Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

### Material

- halogen-free
- phosphor-free
- silicone-free
- cadmium-free

Shell: Polyamide PA 6  
Seal: Neoprene

### Properties

- Optimum strain relief through clamping plates
- Easy to assemble
- Large clamping areas

### Technical Data

Protection classification: IP 68 - 5 bar

Temperature range: -30°C to +80°C

Test standard: EN50262

### Note

Details on the individual tests appear in section "Technical Information".

### metric thread

Part No. light grey RAL 7035	Part No. dark grey RAL 7001	Part No. black RAL 9005	Size Metr.	Cable-Ø from / to mm	Thread length mm	Spanner size mm	Unit	net EUR/100 items at acceptance of		
								up to 100	101 - 500	501 - 1000
93908	93923	93937	M 12 x 1,5	3,0 - 6,5	8,0	15	100	o. r.	o. r.	o. r.
93909	93924	93938	M 16 x 1,5	4,0 - 8,0	8,0	19	50	o. r.	o. r.	o. r.
92667	92668	92669	M 16 x 1,5	5,0 - 10,0	10,0	22	50	o. r.	o. r.	o. r.
93910	93925	93939	M 20 x 1,5	6,0 - 12,0	10,0	24	50	o. r.	o. r.	o. r.
93911	93926	93940	M 25 x 1,5	11,0 - 17,0	8,0	29	50	o. r.	o. r.	o. r.
93912	93927	93941	M 32 x 1,5	15,0 - 21,0	10,0	36	25	o. r.	o. r.	o. r.
93913	93928	93942	M 40 x 1,5	19,0 - 28,0	10,0	46	20	o. r.	o. r.	o. r.
93914	93929	93943	M 50 x 1,5	28,0 - 38,0	18,0	60	10	o. r.	o. r.	o. r.
93915	93930	93944	M 63 x 1,5	34,0 - 44,0	18,0	65	10	o. r.	o. r.	o. r.

### metric thread - with reducing seal

Part No. light grey RAL 7035	Part No. dark grey RAL 7001	Part No. black RAL 9005	Size Metr.	Cable-Ø from / to mm	Thread length mm	Spanner size mm	Unit	net EUR/100 items at acceptance of		
								up to 100	101 - 500	501 - 1000
903532	903542	903552	M 12 x 1,5	2,0 - 5,0	8,0	15	100	o. r.	o. r.	o. r.
903533	903543	903553	M 16 x 1,5	3,0 - 7,0	10,0	22	50	o. r.	o. r.	o. r.
903534	903544	903554	M 20 x 1,5	5,0 - 9,0	10,0	24	50	o. r.	o. r.	o. r.
903535	903545	903555	M 25 x 1,5	9,0 - 13,0	8,0	29	50	o. r.	o. r.	o. r.
903536	903546	903556	M 32 x 1,5	11,0 - 15,0	10,0	36	25	o. r.	o. r.	o. r.
903537	903547	903557	M 40 x 1,5	14,5 - 25,0	10,0	46	20	o. r.	o. r.	o. r.
903538	903548	903558	M 50 x 1,5	24,0 - 31,0	18,0	60	10	o. r.	o. r.	o. r.
903539	903549	903559	M 63 x 1,5	29,0 - 35,0	18,0	65	10	o. r.	o. r.	o. r.

Continuation ►

o. r. = on request