

DESCRIPTION: 2 CONDUCTOR 18 AWG TPE INSULATED CABLE,
FOIL AND BRAID SHIELDED WITH PVC JACKET
UL AND CSA RATED

CONDUCTOR: 18 AWG 16 STRANDS TINNED ANNEALED COPPER IN ACCORDANCE
WITH ASTM B-3 AND B-8

DIELECTRIC: .017" NOMINAL WALL THICKNESS PVC TO DIAMETER OF .080"

COLOR CODE: BLACK, RED

CABLE ASSEMBLY:

LAY LENGTH: 3" NOMINAL LEFT HAND DIRECTION
FILLER: NONE REQUIRED
BINDER: .001" NOMINAL THICKNESS POLYESTER
FOIL SHIELD: .0015" NOMINAL THICKNESS ALUMINUM/POLYESTER/ALUMINUM TAPE
DRAIN: 18 AWG 16 STRAND TINNED COPPER UNDER FOIL SHIELD

JACKET:

MATERIAL: THERMOPLASTIC TPE
COLOR: BLACK
WALL THICKNESS: .037" NOMINAL
FINISHED CABLE DIAMETER: .265" NOMINAL

705360

CABLE IDENTIFICATION:

TYPE: SURFACE PRINT ON JACKET
INK COLOR: CONTRASTING TO JACKET
LEGEND: "E95534 18 AWG TYPE PLTC (UL) 90C OR AWM 20237 125C 300V -- LL91737
CSA AWM I/IIA/B125 300V FT1"

[Handwritten Signature] 5/15/08
ING- PROJECT.
ROMAN SIERRA

DATA GUIDE

CABLE CORP.

ONE ERNRIC PLACE
GARDNER, MA. 01440
978-632-0900

REV.	DESCRIPTION	DATE	APP.
1	ADD PLTC RATING	5/14/08	
-	INITIAL RELEASE	5/7/07	

TITLE 18 AWG 2/C TPE/TPE SHIELD CABLE			
SCALE	P/N 07D24-9	REV	
DATE 5/07	DRN. BY WJC	APP. BY	