



NOTES:

1. CORD PER BODINE MANUFACTURING STANDARD #CPS-20-1
2. CORD MUST CONFORM TO UL 758 & CSA C22.2 NO. 210
3. THE FOLLOWING MINIMUM INFORMATION IS TO BE LEGIBLY PRINTED [OR INDENTED] AT INTERVALS OF 24" OR LESS.
 - MFR'S IDENTIFYING MARK OR U.L. FILE No.
 - CORD TYPE LETTER DESIGNATION.
 - NUMBER & SIZE OF CONDUCTORS.
 - TEMPERATURE RATING
 - VOLTAGE RATING
4. WIRE BUILD IS TWO TWISTED PAIRS WITH 1.75" LAY
5. MUST BE UL AWM STYLE PLTC AND CSA TYPE CMG FT4

PART NO./REV. 49001033 E	
CORD BULK PVC 18/4 105C PLTC BRSHLD	
CORD BULK 4 CONDUCTOR BRAID SHIELD	
GRAPHIC NO: 490AA024.B	DESIGNER: JON/HKN
eDOC NO: 20110648	SCALE: NONE
	PHASE-IN DATE: 12/30/2079
	PHASE-OUT DATE: 12/31/2079
UNLESS OTHERWISE SPECIFIED: UNITS ARE IN INCHES [mm]	
TOLERANCES: .XX:±.01 .XXX:±.005 ANGLES: X'±3' X.X':±0.5'	
BODINE ELECTRIC COMPANY	

BRAIDED SHIELD

AWG:	15 AWG [EQUIV. REF.]
STRAND AWG:	36
NO. OF STRANDS:	168 REF.
MATERIAL:	COPPER
FINISH:	TINNED

INSULATION

DIAMETER:	.080 NOM
MATERIAL:	300
VOLTAGE RATING:	300
U/L & CSA TEMP RATING:	105°C
HI-POT TEST REQTS:	1800 VAC 60 HZ FOR 1 SECOND

JACKET

DIAMETER:	.310/0.330
TYPE:	PLTC
COLOR:	GRAY
UL & CSA TEMP. RATING	105°C

CONDUCTOR

AWG:	18
STRAND AWG:	19
NO. OF STRANDS:	30
MATERIAL:	COPPER
FINISH:	TINNED

