

DESCRIPTION: 2 CONDUCTOR 22 AWG TPE INSULATED CABLE,
UNSHIELDED WITH TPE JACKET
UL AND CSA RATED

CONDUCTOR: 22 AWG 7 STRANDS TINNED ANNEALED COPPER IN ACCORDANCE
WITH ASTM B-3 AND B-8

DIELECTRIC: .016" NOMINAL WALL THICKNESS TPE TO DIAMETER OF .062"

COLOR CODE: BLACK, BROWN

CABLE ASSEMBLY:

LAY LENGTH: 2" NOMINAL LEFT HAND DIRECTION
BINDER: .001" NOMINAL THICKNESS POLYESTER TAPE

JACKET:

MATERIAL: THERMOPLASTIC TPE
COLOR: BLACK
RIPCORD: NYLON PULLED UNDER JACKET
WALL THICKNESS: .042" NOMINAL
FINISHED CABLE DIAMETER: .211" NOMINAL

CABLE IDENTIFICATION:

TYPE: SURFACE PRINT ON JACKET
INK COLOR: WHITE
LEGEND: "E95534 22 AWG TYPE PLTC (UL) 90C OR AWM 20237 125C
300V --- LL91737 CSA AWM IA/B IIA/B 125C 300V FT1"

DATA GUIDE

CABLE CORP.

ONE ERNRIC PLACE
GARDNER, MA. 01440
978-632-0900

REV	DESCRIPTION	DATE	APP.
-	INITIAL RELEASE	3/12/10	

TITLE
22 AWG 2/C BLK TPE/TPE PLTC CABLE

SCALE P/N REV
06H24-2

DATE DRN. BY APP. BY
3/10 WJD