

9527 Paired - 300V Power-Limited Tray Cable

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : ICEA Table E2.pdf</p>
--	--

Description:

22 AWG pairs stranded (7x30) tinned copper conductors, twisted pairs, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	27
Total Number of Conductors	54
AWG	22
Stranding	7x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	F-R PVC - Flame Retardant Polyvinyl Chloride
Insulation Diameter	.062 in.

Pair Color Code Chart :

Number	Color	Number	Color
1	Black & Red and Numbered	15	Black & Red and Numbered
2	Black & Red and Numbered	16	Black & Red and Numbered
3	Black & Red and Numbered	17	Black & Red and Numbered
4	Black & Red and Numbered	18	Black & Red and Numbered
5	Black & Red and Numbered	19	Black & Red and Numbered
6	Black & Red and Numbered	20	Black & Red and Numbered
7	Black & Red and Numbered	21	Black & Red and Numbered
8	Black & Red and Numbered	22	Black & Red and Numbered
9	Black & Red and Numbered	23	Black & Red and Numbered
10	Black & Red and Numbered	24	Black & Red and Numbered
11	Black & Red and Numbered	25	Black & Red and Numbered
12	Black & Red and Numbered	26	Black & Red and Numbered
13	Black & Red and Numbered	27	Black & Red and Numbered
14	Black & Red and Numbered		

OUTER SHIELD:

9527 Paired - 300V Power-Limited Tray Cable

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	7x30
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	F-R PVC - Flame Retardant Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.063 in.
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.763 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +105°C
UL Temperature Rating	105°C
Bulk Cable Weight	280 lbs/1000 ft.
Max. Recommended Pulling Tension	500 lbs.
Min. Bend Radius (Install)	7.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	PLTC, ITC, CMG
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

FLAME TEST:

UL Flame Test	UL1685 FT4 Loading
C(UL) Flame Test	FT4
IEEE Flame Test	1202
ICEA Flame Test	T-29-520

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Sunlight Resistance	Yes

PLENUM/NON-PLENUM:

9527 Paired - 300V Power-Limited Tray Cable

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Inductance	.21 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	26 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	45 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	15 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	15 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	2.4 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9527 0601000	27 PR #22 PVC SHLD PVC	1000	321	CHROME	C Z
9527 060500	27 PR #22 PVC SHLD PVC	500	156.5	CHROME	C

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 09-20-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.