COMMSCOPE®

Category 6 and 5e Dynamic Angle Right/Left Patch Panels

CommScope's dynamic angle right/left panels offer superior performance and flexibility. Unlike fixed-angle panels, CommScope's patented solution combines the ability to dynamically angle connections either right or left in a low profile, high density design. Forty-five degree silver-plated IDCs can be punched down with either a standard 110 or KRONE termination tool.

Features:

- Patented rotating modules ease stress on patch cords allowing for improved cable management

- Low profile dynamic angling allows for greater flexibility and use in cabinet environments

- UL 1863 certified

- Conductors can be terminated with either a KRONE or 110 tool

- Forty-five degree silver-plated IDCs provide secure, reliable gas-tight connection

- Includes adhesive paper labels for station identification

- Universal wiring label for easy termination to either T568A or T568B

- Rear cable manager included

Category 6 and 5e Dynamic Angle
Right/Left Patch Panels

Back view with cable management bar

Specifications

Performance:	ANSI/TIA-568-C.2 Category 5e or 6, ISO 11801 Class D, E
Applications Supported:	10Base-T, 100Base-TX, 1000Base-T, E1, T1
Front Interface:	UTP RJ45
Rear Interface:	KRONE LSA-PLUS® (110 tool compatible)
Weight:	0.544 kg/1.2 lbs
Rack Mounting:	19" EIA
Safety:	UL, cUL, CE, EN 60950
Operating Temperature:	0° to 40° C (32° to 104° F)
Storage Temperature:	-20° to 70° C (-4° to 158° F)

Ordering Information

Description	Quantity	Dimensions (HxWxD)	Ordering Number
24-port Category 6 angle right/left patch panel, T568A/B compatible	1	44.45 mm x 482.6 mm x 38.1 mm (1.75" x 19" x 1.5")	PP24AC6T
48-port Category 6 angle right/left patch panel, T568A/B compatible	1	88.9 mm x 482.6 mm x 38.1 mm (3.5" x 19" x 1.5")	PP48AC6T
24-port Category 5e angle right/left patch panel, T568A/B compatible	1	44.45 mm x 482.6 mm x 38.1 mm (1.75" x 19" x 1.5")	PP24AC5ET
48-port Category 5e angle right/left patch panel, T568A/B compatible	1	88.9 mm x 482.6 mm x 38.1 mm (3.5" x 19" x 1.5")	PP48AC5ET
Rear cable management bar		44.45 mm x 482.6 mm x 101.6 mm (1.75" x 19" x 4")	ADCCMR-A
ID tabs (icons)	25 per bag		ADCICBXX*

*Replace XX with: 03 = Red 09 = Yellow 04 = Green 10 = Purple 05 = Blue 11 = Brown 08 = Orange

COMMSCOPE®