




Ring Terminals, Vinyl Insulated – Funnel Entry

Type PV-RB

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Ring tongue design assures a secure connection in high vibration applications
- Insulation support helps to prevent wire damage in bending applications
- UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B



| Part Number | Wire Range | Color Code | Stock Thickness (In.) | Max Ins. (In.) | Stud Size | Figure Dimensions (In.) | | | CA9 Series Crimp Die | CA-800/EZ Series Crimp Die | Pieces Per Reel | | | | | | |
|--------------|-------------|------------|-----------------------|----------------|-------------|-------------------------|------|-------|----------------------|----------------------------|-----------------|------|--------|----------|--------|----------|------|
| | | | | | | L | W | C | | | | | | | | | |
| PV18-4RNB-3K | 22 – 18 AWG | Red | 0.03 | 0.150 | #4 | 0.74 | 0.21 | 0.19 | CD9-1A | CD-800-1 | 3000 | | | | | | |
| PV18-4RB-3K | | | | | #4 | 0.78 | 0.25 | 0.20 | | | 3000 | | | | | | |
| PV18-6RNB-3K | | | | | #6 | 0.75 | 0.23 | 0.19 | | | 3000 | | | | | | |
| PV18-6RB-3K | | | | | #6 | 0.78 | 0.25 | 0.20 | | | 3000 | | | | | | |
| PV18-8RB-3K | | | | | #8 | 0.86 | 0.31 | 0.25 | | | 3000 | | | | | | |
| PV18-10RB-3K | | | | | #10 | 0.86 | 0.31 | 0.25 | | | 3000 | | | | | | |
| PV18-14RB-3K | | | | | 1/4" | 1.06 | 0.45 | 0.38 | | | 3000 | | | | | | |
| PV18-56RB-2K | | | | | 5/16" | 1.06 | 0.46 | 0.38 | | | 2000 | | | | | | |
| PV18-38RB-2K | | | | | 3/8" | 1.15 | 0.53 | 0.43 | | | 2000 | | | | | | |
| PV14-4RB-3K | | | | | 16 – 14 AWG | Blue | 0.03 | 0.170 | | | #4 | 0.76 | 0.25 | 0.22 | CD9-2A | CD-800-2 | 3000 |
| PV14-6RNB-3K | #6 | 0.76 | 0.25 | 0.22 | | | | | 3000 | | | | | | | | |
| PV14-6RB-3K | #6 | 0.86 | 0.31 | 0.25 | | | | | 3000 | | | | | | | | |
| PV14-8RB-3K | #8 | 0.86 | 0.31 | 0.25 | | | | | 3000 | | | | | | | | |
| PV14-10RB-3K | #10 | 0.86 | 0.31 | 0.25 | | | | | 3000 | | | | | | | | |
| PV14-14RB-3K | 1/4" | 1.05 | 0.45 | 0.38 | | | | | 3000 | | | | | | | | |
| PV14-56RB-2K | 5/16" | 1.06 | 0.46 | 0.38 | | | | | 2000 | | | | | | | | |
| PV14-38RB-2K | 3/8" | 1.15 | 0.53 | 0.43 | | | | | 2000 | | | | | | | | |
| PV10-6RB-2K | 12 – 10 AWG | Yellow | 0.04 | 0.225 | | | | | #6 | 1.02 | 0.31 | 0.31 | CD9-3B | CD-800-3 | | | 2000 |
| PV10-8RB-2K | | | | | | | | | #8 | 1.02 | 0.31 | 0.31 | | | | | 2000 |
| PV10-10RB-2K | | | | | #10 | 1.02 | 0.31 | 0.31 | 2000 | | | | | | | | |
| PV10-14RB-2K | | | | | 1/4" | 1.20 | 0.52 | 0.38 | 2000 | | | | | | | | |
| PV10-56RB-2K | | | | | 5/16" | 1.20 | 0.52 | 0.38 | 2000 | | | | | | | | |
| PV10-38RB-2K | | | | | 3/8" | 1.23 | 0.58 | 0.43 | 2000 | | | | | | | | |

B1.
Cable
Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Cable
Ties &
Accessories

C1.
Wiring
Duct

C2.
Abrasion
Protection

C3.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
&
Write-On
Markers

E4.
Permanent
Identification

E5.
Industrial
Safety
Solutions

F.
Keystone
Cabling
Systems

G.
Part
Number
Index