

## 1. PART NUMBER AND CHARACTERISTICS

AMP Part No	Rev	Color	Size	Expanded ID	Recovered Wall Thickness
17373-1	D	White	.375	.750	.030
17373-2	D	Brown	.188	.375	.025
17373-3	D	Black	.047	.093	.020
17373-4	D	Clear	.047	.093	.020
17373-5	D	White	.047	.093	.020
17373-6	D	Black	.062	.125	.020
17373-7	D	Brown	.062	.125	.020
17373-8	D	Red	.062	.125	.020
17373-9	D	Orange	.062	.125	.020
1-17373-0	D	Yellow	.062	.125	.020
1-17373-1	D	Green	.062	.125	.020
1-17373-2	D	Blue	.062	.125	.020
1-17373-3	D	Brown	.093	.187	.020
1-17373-4	D	Red	.093	.187	.020
1-17373-5	D	Yellow	.093	.187	.020
1-17373-6	D	Green	.093	.187	.020
1-17373-7	D	White	.093	.187	.020
1-17373-8	D	Black	.125	.250	.025
1-17373-9	D	Brown	.125	.250	.025
2-17373-0	D	Red	.125	.250	.025
2-17373-1	D	Orange	.125	.250	.025
2-17373-2	D	Yellow	.125	.250	.025
2-17373-3	D	Green	.125	.250	.025
2-17373-4	D	Blue	.125	.250	.025
2-17373-5	D	Violet	.125	.250	.025
2-17373-6	D	Gray	.125	.250	.025
2-17373-7	D	White	.125	.250	.025
2-17373-8	D	Clear	.125	.250	.025
2-17373-9	D	Black	.187	.375	.025
3-17373-0	D	Red	.187	.375	.025
3-17373-1	D	Orange	.187	.375	.025
3-17373-2	D	Yellow	.187	.375	.025
3-17373-3	D	Green	.187	.375	.025
3-17373-4	D	Blue	.187	.375	.025
3-17373-5	D	Violet	.187	.375	.025

This specification is a controlled document.				<b>COMMERCIAL ITEM SPECIFICATION</b>							
MATERIAL Polyolefin				DR J. N. Burr		29MAR96		<b>AMP</b> AMP Incorporated Harrisburg, PA 17105-3608			
FINISH -----				CHK E. Meyers		01APR96					
				APP D. E. Crabb		02APR96		NO <b>17373</b>	REV <b>H</b>	LOC <b>B</b>	DIST <b>31</b>
				SHEET 1 OF 2		TITLE <b>TUBING, HEAT SHRINKABLE</b>					
H	EC 0990-0289-97	FO	04APR97								
REV	REVISION RECORD	APP	DATE								

1. PART NUMBER AND CHARACTERISTICS (Continued)

AMP Part No	Rev	Color	Size	Expanded ID	Recovered Wall Thickness
3-17373-6	D	Gray	.187	.375	.025
3-17373-7	D	White	.187	.375	.025
3-17373-8	D	Clear	.187	.375	.025
3-17373-9	D	Black	.250	.500	.025
4-17373-0	D	Brown	.250	.500	.025
4-17373-1	D	Red	.250	.500	.025
4-17373-2	D	Orange	.250	.500	.025
4-17373-3	D	Yellow	.250	.500	.025
4-17373-4	D	Green	.250	.500	.025
4-17373-5	D	Blue	.250	.500	.025
4-17373-6	D	Black	.375	.750	.030
4-17373-7	D	Brown	.375	.750	.030
4-17373-8	D	Red	.375	.750	.030
4-17373-9	D	Yellow	.375	.750	.030
5-17373-0	D	Green	.375	.750	.030
5-17373-1	D	Gray	.375	.750	.030
5-17373-2	D	Black	.500	1.000	.035
5-17373-3	D	White	.250	.500	.025
5-17373-4	D	Black	.023	.046	.016
5-17373-5	D	Brown	.023	.046	.016
5-17373-6	D	Red	.023	.046	.016
5-17373-7	D	Orange	.023	.046	.016
5-17373-8	D	Yellow	.023	.046	.016
5-17373-9	D	Green	.023	.046	.016
6-17373-0	D	Blue	.023	.046	.016
6-17373-1	D	Violet	.023	.046	.016
6-17373-2	D	Gray	.023	.046	.016
6-17373-3	D	White	.023	.046	.016
6-17373-4	E	Black	.750	1.500	.040
6-17373-5	E	Red	.750	1.500	.040
6-17373-6	E	Black	1.000	2.000	.050
6-17373-7	E	Red	.500	1.000	.035
6-17373-8	E	Black	.093	.187	.020
6-17373-9	E	Blue	.093	.187	.020
7-17373-0	F	White	.375	.750	.030
7-17373-1	G	Green	.047	.093	.020
7-17373-2	G	Red	.047	.093	.020

- 1.1. All dimensions are nominal unless otherwise specified
- 1.2. Shrinkage temperature: 120°C
- 1.3. Type: CPX100 Thin Wall
- 1.4. Shrink ratio: 2:1
- 2. RECOMMENDED MANUFACTURER  
U.S. CANUSA-EMI  
Cincinnati, OH  
or AMP Engineering approved equivalent