

# UL Style 3357

## Appliance Wiring

90°C - 5000 volts AC - Horizontal Flame

### Features

Conductors available in solid or stranded, tinned or copper  
 Insulation: 90°C EPDM  
 RoHS and REACH Compliant

### Compliances

Voltage Rating 5000 volts AC  
 Horizontal Flame per UL 1581  
 UL 758

### Product Design Options

Custom strand constructions  
 Custom diameter to meet design criteria  
 Various colors for base and stripe combinations  
 Packaging options: reels, drums, returnable containers

### Applications

Test probe leads for electrical and electronic  
 measuring and test equipment

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (In)	Nom OD (In)	Min Wall (In)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
18	65	36	0.046	0.140	0.040	15	5
14	19	27	0.071	0.164	0.036	24	13

### Customer Service Group

1 Prestolite Drive  
 Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: [www.Prestolitewire.com](http://www.Prestolitewire.com)

Email: [bulkwiresales@prestolitewire.com](mailto:bulkwiresales@prestolitewire.com)

