



Standard Welding Cable

125°C EPDM

Features

Conductors available in tinned or copper
Insulation: 125°C EPDM
RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors
Packaging options: reels

Applications

Cables used for welding electrical

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Nom. Wall (in)	Min. Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
6	266	30	0.194	0.323	0.060	0.042	111	79
4	392	30	0.211	0.375	0.060	0.046	164	115
3	525	30	0.248	0.377	0.060	0.042	196	154
2	672	30	0.284	0.424	0.060	0.046	248	197
1	779	30	0.346	0.510	0.080	0.056	315	243
1/0	1026	30	0.391	0.561	0.080	0.056	403	320
2/0	1330	30	0.434	0.606	0.080	0.056	482	390
3/0	1672	30	0.442	0.619	0.080	0.056	587	491
4/0	2052	30	0.547	0.728	0.080	0.056	721	602
250MCM	2368	30	0.577	0.825	0.115	0.081	942	764

REV: -1- 3/30/2011

Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.prestolitewire.com