



# ABS

## Anti-Lock Braking Cables

105°C to 150°C

### Features

Insulation: 105°C PVC, 125°C/150°C PYET  
 Conductors available in tinned, Percon or copper

### Compliances

RoHS compliant

### Product Design Options

Custom strand constructions  
 Custom diameter to meet design criteria  
 Various colors inners for base and stripe combinations  
 Packaging option: reels

### Applications

Electrical system wiring for anti-lock braking cable

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Number of Primary Conductors	Nom OD (in)	Min Avg Wall (in)	Nom Jacket OD (in)	Jacket Min Avg wall (in)	Approx. Net Weight (lbs/Mft)	Approx. Cu (lbs/Mft)
24	41	39	0.026	2	0.045	0.008	0.165	0.027	13	3
22	63	40	0.029	2	0.062	0.010	0.177	0.018	16	4
22	7	30	0.029	3	0.062	0.013	0.180	0.010	20	10
20	28	34	0.038	3	0.065	0.009	0.185	0.028	22	6
18	42	34	0.047	4	0.070	0.009	0.244	0.028	43	21

### Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450  
 Phone: 800-952-3842 870-236-8141  
 Fax: 870-239-6139  
 Web: [www.prestolitewire.com](http://www.prestolitewire.com)