



SAE J1128 GPT
Automotive Primary Wire
85°C

Features

Conductors available in tinned or copper
Insulation: 85°C PVC

RoHS and REACH Compliant

Product Design Options

Custom strand constructions
Custom diameter to meet design criteria
Various colors for base and stripe combinations
Packaging options: reels or drums

Compliances

Ford ESB-M1L56-A, Ford ESF-M1L58-A
Ford ESF-M1L56-A

Chrysler MS-3450

Applications

Cables used for automotive electrical

AWG size	Number of Strands	Strand Size (ga)	Nom Cond OD (in)	Nom OD (in)	Min Avg Wall (in)	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
22	7	30	0.030	0.076	0.019	5	30
20	7	28	0.038	0.084	0.019	6	19
18	16	30	0.048	0.092	0.018	8	12
16	19	29	0.056	0.103	0.018	11	7
14	19	27	0.069	0.117	0.018	16	5
12	19	25	0.088	0.144	0.021	25	3
10	19	23	0.108	0.175	0.025	39	2

Customer Service Group

1 Prestolite Drive Paragould, Arkansas 72450

Phone: 800-952-3842 870-236-8141

Fax: 870-239-6139

Web: www.prestolitewire.com