

## SAE J1939-15

### CAN Bus Data Cables

-40°C to 125°C

#### Features

Impedance 108-132 Ω at 1 MHz  
 Insulation: XLPO 125°C, 125°C TPU  
 Resistance: 50 mΩ/m maximum @ 20°C  
 Line delay: 5.0 ns/m nominal  
 Capacitance 75 pF/m maximum  
 Un-shielded twisted pair  
 Reduced physical layer, 250k bits/sec.  
 Abrasion and cut resistant, waterproof 125°C TPU jacket  
 Excellent oil and chemical resistance

#### Product Design Options

Custom strand constructions  
 Custom diameter to meet design criteria  
 Various colors for base and stripe combinations  
 Packaging options: reels, drums, returnable containers  
 Available with or without fillers  
 Insulation option: 150°C

#### Compliances

RoHS compliant  
 SAE J1939-15 Physical media  
 SAE J1128 performance  
 (fluid, flame propagation)

#### Applications

Electrical connection of a number of ECU's  
 (Electronic Control Units) to a reduced network.

Part #	AWG Size	Number of Strands	Strand Size (in)	Nom Cond OD (in)	Filler	Nom OD (in)	Impedance	Capacitance	Approx. Net Weight (lbs/mft)	Approx. Cu (lbs/mft)
149816	18	19	0.0092	0.045	No	0.252	120 ± 10% Ω @ 1 MHz	56 pF/m @ 1MHz	31	10
149821	18	19	0.0092	0.045	Yes	0.254	120 ± 10% Ω @ 1 MHz	48 pF/m @ 1MHz	32	10
149807	20	19	0.00708	0.035	No	0.228	120 ± 10% Ω @ 1 MHz	57 pF/m @ 1MHz	26	7
149812	20	19	0.00708	0.035	Yes	0.235	120 ± 10% Ω @ 1 MHz	50 pF/m @ 1MHz	26	7

#### **Customer Service Group**

1 Prestolite Drive Paragould, Arkansas 72450  
 Phone: 800-952-3842 870-236-8141  
 Fax: 870-239-6139  
 Web: [www.prestolitewire.com](http://www.prestolitewire.com)