

- 2.6 MAXIMUM OVERALL DIAMETER: .160
3. MAXIMUM OPERATING VOLTAGE: 600 VOLTS RMS.
4. OPERATING TEMPERATURE RANGE: MINUS 40 TO PLUS 105 DEGREES CENTIGRADE. THE MINIMUM BEND DIAMETER FOR BEND TEST AT MINUS 40 DEGREES CENTIGRADE IS THREE (3) INCHES.
5. MAXIMUM CAPACITANCE: 28 PICO FARADS PER FOOT BETWEEN CONDUCTORS WITH SHIELD FLOATING. 45 PICO FARADS PER FOOT BETWEEN EACH CONDUCTOR AND SHIELD.
6. IDENTIFY PER MIL-STD-130.
7. QUALITY ASSURANCE PROVISIONS: SHALL MEET THE APPLICABLE REQUIREMENTS OF MIL-W-16878.

SUGGESTED SOURCE(S) OF SUPPLY:

ITT WIRE & CABLE DIV., CLINTON, MASSACHUSETTS
PART NO.:

BRAND-REX DIV. OF AMERICAN ENKA CORP., WILLIMANTIC, CONN.
PART NO.:

TENSOLITE INSULATED WIRE CO., TARRYTOWN, NEW YORK
PART NO.: 22499/207V-2

SIZE	CODE IDENT NO.	NOSC DWG NO.
A	10001	2666264
SCALE NONE	REV A	SHEET