



Specification Sheet

Lake Cable Quote Part #: 182ZC-09HON

- Description:** Two elements zip cord cable with overall integral PVC jacket. (UL) CMG
- 18 AWG 1 conductor 16 Strands Bare copper wire
 - 18 AWG 1 conductor 16 Strands Bare copper wire

Element 1: 18 AWG 1 conductor BC

1. **Conductor**
 - 1.1. AWG Size & Stranding: 18 AWG 16 Strands Class K
 - 1.2. Material: Annealed Bare Copper
 - 1.3. Conductor Count: 1 Conductor

Element 2: 18 AWG 1 conductor BC

2. **Conductor**
 - 2.1. AWG Size & Stranding: 18 AWG 16 Strands Class K
 - 2.2. Material: Annealed Bare Copper
 - 2.3. Conductor Count: 1 Conductor
3. **Assembly**
 - 3.1. Nominal Lay Length: Pulled in parallel at jacketing
4. **Integral Jacket**
 - 4.1. Material: Polyvinylchloride
 - 4.2. Wall Thickness: 0.022"
 - 4.3. Diameter: 0.090" x 0.190"
 - 4.4. Color: White
 - 4.5. Ripcord: No
 - 4.6. Weight: 18 Lbs/Mft

5. **Markings**
 - 5.1. Type: Cable shall be permanently identified via surface inkjet print
 - 5.2. Legend: LAKE CABLE 18 AWG 2/C E171197 (UL) TYPE CMG C(UL)US OR (UL) CL2 75'C
SUN RES FT-4 (WORK ORDER #) DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9
"ROHS"
 - 5.3. Footage Markers: Ascending/Descending
6. **Standards**
 - 6.1. UL listed as type CMG C(UL)US per UL standard 444
 - 6.2. All materials used in the manufacture of this cable are RoHS compliant
 - 6.3. Maximum Operating Voltage: 300V
 - 6.4. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION