

ATLAS WIRE CORPORATION 9525 RIVER STREET SCHILLER PARK, ILLINOIS 60176 (847) 678-1210 (847) 678-1281 FAX info@atlaswirecorp.com



MATERIAL SPECIFICATION SHEET

#20 10/30 TC-BC .017" PVC
ROHS COMPLIANT
2/CONDUCTOR FLAT PARALLEL CONSTRUCTION
RIP CORD – 105c
INDUSTRIAL ELECTRIC PART # RC2002-00AT

ONE

CONDUCTOR: #20 10/30 TINNED COPPER 1/2" SEMI CONCENTRIC

NOMINAL O.D. .038" APPROXIMATE CIRCULAR MILL AREA 1,000

WEIGHT PER THOUSAND FEET 3.20#

BASIC SPECIFICATION ASTM B 174

ONE

CONDUCTOR: #20 10/30 BARE COPPER 1" LAY BUNCHED

NOMINAL O.D. .038"

APPROXIMATE CIRCULAR MILL AREA 1,000
WEIGHT PER THOUSAND FEET 3.20#

BASIC SPECIFICATION ASTM B 174

PVC: TEMPERATURE RATING 105c

VOLTAGE RATING 300v

ELONGATION 330% AVERAGE TENSILE STRENGTH 2,450 PSI AVERAGE

DUROMETER (SHORE) 91 (A)
OXYGEN INDEX 28
SPECIFIC GRAVITY 1.32

SPARK TESTED 3,000 VOLTS

DIMENSIONS: FINISHED NOMINAL O.D. HEIGHT .072"

FINISHED NOMINAL O.D. WIDTH .146" WEIGHT 9.92#

info@atlaswirecorp.com