

- Highly Reflective
- Easy to Install
- Cut And Abrasion Resistant
- Resists Gasoline and **Engine Chemicals**



No special tools or skills required for



See pg. 105 for bike kits.

## Reflective, Split Semi Rigid Sleeving For Easy Installation

Ease of installation makes F6 REFLEX (F6R) the most suitable reflective sleeving for applications where disassembly of the components is not a viable option. Just open the lateral split and slip the sleeving over wires or cables. The sleeving will snap back in place and provide an extra measure of safety under low light conditions.

F6 Reflex is available in clear. Patent pending.

Part

F6R0.19CL

Under low light conditions, the retrored strands in F6 Reflex sleeving reflect ligh 1,500 times more efficiently than bright

Wall

**Thickness** 

0.025"

Standa

**Bulk Sp** 

200

100'

| ool Shop Spool                   | Available<br>Colors | Lbs/<br>100' |  |  |  |  |  |  |
|----------------------------------|---------------------|--------------|--|--|--|--|--|--|
| flective<br>It up to<br>It white | o and a second      |              |  |  |  |  |  |  |


Clear (CL)

0.58

| Ketler   |
|----------|
| o aj agr |
|          |

- Highly Reflective
- Easy to Install
- Expands up to 150%
- Halogen Free
- Resists Gasoline and **Engine Chemicals**

Under low light conditions, the retroreflective strands in FLEXO Reflex sleeving reflect light up to 1,500 times more efficiently than bright



1-973-300-9242 www.techflex.com

## **Reflects** Light 360° Up To 675'

Nominal

Size

3/16"

FLEXO REFLEX (RFN) is our polyethylene terephthalate material braided together with highly reflective 3M Scotchlite retroreflective monofilament. This unique combination provides a high level of wire and cable protection with the added advantage of extraordinary 360 degree, on-axis reflectivity. RFN is up to 1,500 times brighter than plain white under identical conditions and will provide high visibility safety on wires, hoses, cables, bicycle and motorcycle cables, stage wiring, and virtually anything else up to 675' away. Reflective even under low light conditions. Patent pending.

| Nominal Part |           | Expansion Range |        | Standard Spool Put-Ups |            | Available  | Lbs/ |
|--------------|-----------|-----------------|--------|------------------------|------------|------------|------|
| Size         | #         | Min.            | Max.   | Bulk Spool             | Shop Spool | Colors     | 100′ |
| 1/8"         | RFN0.13CL | 1/16"           | 1/4"   | 1,000′                 | 100′       | Clear (CL) | 0.29 |
| 1/4"         | RFN0.25   | 3/16"           | 3/8"   | 1,000′                 | 100′       | CL & BK    | 0.33 |
| 1/2"         | RFN0.50   | 1/4"            | 1"     | 500′                   | 100′       | CL & BK    | 0.52 |
| 3/4"         | RFN0.75   | 3/8″            | 1 3/8″ | 250′                   | 75′        | CL & BK    | 0.63 |

