

Description: 24 AWG 75 OHM COAX CABLE  
Compliance: UL Standards 13, & 444; NEC Articles 725 & 800

#### Construction:

Conductor 24 AWG Solid Bare Copper

#### Insulation

Type Foamed Polyethylene  
Color White  
Thickness 0.034" nom.  
Diameter 0.087" nom.

#### Braid

Strands 0.005" nom. Bare Copper  
% Coverage 95

#### Jacket

Type PVC  
Color Black  
Thickness 0.017" nom.  
Diameter 0.145" nom.

Legend (Ink Print) HONEYWELL P/N 5020 CCTV PREMIUM 75 Ohm 24 AWG 3038058 (ETL) CL2 75C  
SUN RES (RoHS) W/O# XXXXXX-XXX XXXX FT CAMERA/ZONE A B C D E F  
1 2 3 4 5 6 7 8 9

#### Properties

Temperature Rating -20 to 75 °C  
Voltage Rating 300 Volts  
Capacitance 17 pf/ft nom.  
Impedance 75 Ohms nom.  
Resistance 26 Ohms/M' at 20°C  
Attenuation (db/100') -0.5 at 1 MHz, -9.4 at 400 MHz, -15.6 at 1000 MHz  
Flame Ratings UL 1685 Vertical Tray Flame