

Part Number: 4-4061QS

Description: BLACK RG 6/U Quad Shield CM rated with 60% and 40% aluminum braids.

Suitable Application: CATV, CM

Physical Characteristics:

Awg	18
Stranding	Single strand
Conductor Material	Copper Coated Steel
Dielectric Material	Gas Injected Foam PE
Nominal Diameter	.178"
1 st Braid Composition	
Tape material	Bonded Aluminum/polyester/aluminum tape
Braid Awg	34
Braid Material	Aluminum
Braid Coverage	60%
Nominal Diameter	.208"
2 nd Braid Composition	
Tape Material	Aluminum/ Mylar/Aluminum
Second braid awg	34
Second Braid Material	Aluminum
Second Braid Coverage	40%
Nominal Diameter	.238"
Final Jacket Material	Sunlight Resistant Black Polyvinylchloride
Nominal Thickness	.031"
Nominal Diameter	.300"
Steel Messenger	N/A

INKJET PRINT:

RG 6/U QUAD SHIELD 18 AWG TYPE CATV OR CM (UL) OR c(UL) CM E179332 SWEEPTESTED TO 3.0 GHZ

Nominal Attenuation:

Impedance:	75 Ohms
Capacitance	16.2 pF/foot
Velocity of Prop	83%

Applicable Standards:

UL Type	CATV,CM
ROHS Compliant	Yes

Attenuation

Frequency	Nom db/100
55	1.4
211	2.6
500	4.1
862	5.5
1000	6.0
2250	10.1
3000	11.0

Customer Name: _____ Date Signed: _____

Customer Approval: _____

Specification Issue Date: 1/28/10