

For more Information
please call

1-800-Belden1



General Description:

19 AWG stranded (7x27) bare copper conductor, gas-injected foam HDPE insulation, double tinned copper braid shield (95% coverage), PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	19	7x27	BC - Bare Copper	1.016

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
Gas-injected FHDPE - Foam High Density Polyethylene	4.572

Outer Shield

Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Braid	TC - Tinned Copper	95.000
2	Braid	TC - Tinned Copper	95.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 7.010 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 74.410 Kg/Km

Max. Recommended Pulling Tension: 515.991 N

Min. Bend Radius/Minor Axis: 69.850 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

RG Type: 6/U

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 1695A

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Inductance:

Inductance (µH/m)
0.347786

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
53.1522

Nominal Velocity of Propagation:

VP (%)
81

Nominal Delay:

Delay (ns/m)
4.10125

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
27.8885

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
5.5777

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1.000	0.787
3.580	1.476
5.000	1.772
6.000	1.805
7.000	2.034
10.000	2.362
12.000	2.723
25.000	3.872
67.500	6.234
71.500	6.562
88.500	7.218
100.000	7.874
135.000	9.187
143.000	9.515
180.000	10.827
270.000	13.124
360.000	15.421
540.000	19.358
720.000	22.639
750.000	22.967
1000.000	26.904
1500.000	34.122
2000.000	40.356
2250.000	43.309
3000.000	51.184
4500.000	64.964

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Operating Voltage - Non-UL:

METRIC MEASUREMENT VERSION

1694F Coax - Low Loss Serial Digital Coax

Voltage
300 V RMS

Other Electrical Characteristic 1: Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination. 75 +/- 1.5 Ohms

Other Electrical Characteristic 2: Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

Minimum Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5	850	20
850	4500	15

Sweep Test

Sweep Testing: 100% Sweep tested 5 MHz to 4.5 GHz.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1694F B591000	305 MT	24.494 KG	BLACK, MATTE	C	#19 GIFHDLPE DBLB FRPVC
1694F G7V1000	305 MT	24.494 KG	RED, MATTE	C	#19 GIFHDLPE DBLB FRPVC
1694F G7W1000	305 MT	24.494 KG	GREEN, MATTE	C	#19 GIFHDLPE DBLB FRPVC
1694F G7X1000	305 MT	24.494 KG	BLUE, MATTE	C	#19 GIFHDLPE DBLB FRPVC
1694F G7Y1000	305 MT	24.494 KG	WHITE, MATTE	C	#19 GIFHDLPE DBLB FRPVC
1694F G8L1000	305 MT	24.494 KG	ORANGE, MATTE	C	#19 GIFHDLPE DBLB FRPVC
1694F G8M1000	305 MT	24.494 KG	YELLOW, MATTE	C	#19 GIFHDLPE DBLB FRPVC
1694F Z4B1000	305 MT	24.494 KG	VIO Z4B	C	#19 GIFHDLPE DBLB FRPVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 11 Revision Date: 08-01-2013

© 2014 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.