

Description: Twenty-Four 18 AWG Conductors
 Overall PVC Jacket

Date: 3/29/2007

JM Part Number: TBD
Reference: IV18C0241202

Components Twenty-Four 18 AWG PVC Insulated Conductors

Conductor: 18 AWG, 16/30 bare copper

Insulation: .016" nominal wall of PVC (see color code)

Jacket: .005" nominal wall of Clear Nylon .089"

Overall Cable Construction

Cabling: Core: Fibrillated Polypropylene
 Layer 1: Nine Conductors
 Layer 2: Fifteen Conductors

Binder: .008" SBR Coated Polyester tape

Jacket: .065" nominal wall of Yellow PVC .690"

Print

**DEMAG CRANES & COMPONENTS CORP P/N 13190549 E66498 24/C 18 AWG
 (UL) TYPE MTW 90C 600V --- LL41103 CSA AWM I/II A/B 90C 600V FT4**

Color Code

Example of numerical print: **24 - TWENTY-FOUR**

1 thru 24: Black and numerically printed

Requirements

Temperature: 90°C
 Voltage: 600V

Approvals: UL Type MTW
 CSA AWM, FT4
 RoHS Compliant

Written By:	rjc	3/29/2007	Rev. 0	Initial Issue
Revised By:	rjc	4/2/2007	Rev. 1	Revised Nominal Finished Cable OD
Revised By:	rjc	4/5/2007	Rev. 2	Revised print legend per customer request
Revised By:				