

homeSELECT™ Duplex and Single Receptacles

Switches and Receptacles



Provides branch circuit convenience power in duplex and single configurations.

- Smooth indented face appearance.
- Terminal screws accepts up to #12 AWG.
- Duplex ultrasonically welded.

- Push wire designed for #14 AWG solid copper wire only.
- Operating temperature: -20°C to 60°C.
- UL Listed E2186, CSA Certified.



Duplex and Single Receptacles

Description	Color	Weather and Tamper-Resistant Catalog Numbers	Tamper-Resistant Catalog Numbers	Standard Catalog Numbers
Duplex Receptacle, 2 Pole, 3 Wire, Grounding, Push and Side Wire Terminations 15A 125V NEMA 5-15R	Almond	—	—	RR15AL
	Black	—	—	RR15BK
	Brown	—	—	RR15
	Ivory	—	—	RR15I
	Light Almond	—	—	RR15LA
	White	—	—	RR15W
Duplex Receptacle, 2 Pole, 3 Wire, Self-Grounding, Push and Side Wire Terminations 15A 125V NEMA 5-15R	Almond	RR15SALWRTR	RR15SALTR	RR15SAL
	Brown	RR15SWRTR	RR15STR	RR15S
	Black	RR15SBKWRTR	RR15SBKTR	RR15SBK
	Ivory	RR15SIWRTR	RR15SITR	RR15SI
	Light Almond	RR15SLAWRTR	RR15SLATR	RR15SLA
	White	RR15SWWRTR	RR15SWTR	RR15SW
Duplex Receptacle, Without Ears, 2 Pole, 3 Wire, Grounding, Eight Push Wire Holes Only #14 AWG 15A 125V NEMA 5-15R	Almond	—	RR15EALTR	RR15EAL
	Black	—	RR15EBKTR	RR15EBK
	Brown	—	RR15ETR	RR15E
	Gray	—	RR15EGYTR	RR15EGY
	Ivory	—	RR15EITR	RR15EI
	Light Almond	—	RR15ELATR	RR15ELA
	White	—	RR15EWTR	RR15EW
Duplex Receptacle, Without Ears, 2 Pole, 3 Wire, Grounding, Push and Side Wire Terminations 100 Per Case, Bulk Packed Mounting Screws Inserted into Strap 15A 125V NEMA 5-15R	Almond	—	RR15KALTR	RR15KAL
	Brown	—	RR15KTR	RR15K
	Ivory	—	RR15KITR	RR15KI
	Light Almond	—	RR15KLATR	RR15KLA
	White	—	RR15KWTR	RR15KW
Single Receptacle, 2 Pole, 3 Wire, Self-Grounding, Side Wire Terminations 15A 125V NEMA 5-15R	Almond	RR151ALWRTR	RR151ALTR	RR151AL
	Black	RR151BKWRTR	RR151BKTR	RR151BK
	Brown	RR151WRTR	RR151TR	RR151
	Gray	RR151GYWRTR	RR151GYTR	RR151GY
	Ivory	RR151IWRTR	RR151ITR	RR151I
	Light Almond	RR151LAWRTR	RR151LATR	RR151LA
	White	RR151WWRTR	RR151WTR	RR151W
Single Receptacle, 2 Pole, 3 Wire, Self-Grounding, Side Wire Terminations 15A 250V NEMA 6-15R	Almond	RR155ALWR	—	RR155AL
	Black	RR155BKWR	—	RR155BK
	Brown	RR155WR	—	RR155
	Gray	RR155GYWR	—	RR155GY
	Ivory	RR155IWR	—	RR155I
	Light Almond	RR155LAWR	—	RR155LA
	White	RR155WWR	—	RR155W
Single Receptacle, 2 Pole, 3 Wire, Self-Grounding, Side Wire Terminations 20A 125V NEMA 5-20R	Almond	RR201ALWRTR	RR201ALTR	RR201AL
	Black	RR201BKWRTR	RR201BKTR	RR201BK
	Brown	RR201WRTR	RR201TR	RR201
	Gray	RR201GYWRTR	RR201GYTR	RR201GY
	Ivory	RR201IWRTR	RR201ITR	RR201I
	Light Almond	RR201LAWRTR	RR201LATR	RR201LA
	White	RR201WWRTR	RR201WTR	RR201W
Single Receptacle, 2 Pole, 3 Wire, Self-Grounding, Side Wire Terminations 20A 250V NEMA 6-20R	Almond	RR205ALWR	—	RR205AL
	Black	RR205BKWR	—	RR205BK
	Brown	RR205WR	—	RR205
	Gray	RR205GYWR	—	RR205GY
	Ivory	RR205IWR	—	RR205I
	Light Almond	RR205LAWR	—	RR205LA
	White	RR205WWR	—	RR205W



Note: *Refer to Technical section X, page X-8 for TR and WR descriptions.

