

## UL Selection Guide

Product Description	AWG/Stranding	Standard Colors	Specification
Irradiated Polyolefin <b>Temperature:</b> 125°C <b>Voltage:</b> 150 Volts UL and CSA Listed	28-16 Various Strandings	Contact for Availability	UL 3265, CSA
Irradiated Polyolefin <b>Temperature:</b> 125°C <b>Voltage:</b> 300 Volts UL and CSA Listed	28/07	Contact for Availability	UL 3266, CSA
	26/07		
	24/07		
	22/07		
	22/19	2	
	20/07	Contact for Availability	
	20/19	2	
	18/19	2, 8, 9	
16/19	2		
Irradiated Polyolefin <b>Temperature:</b> 125°C <b>Voltage:</b> 600 Volts UL and CSA Listed	28-4/0 Various Strandings	Contact for Availability	UL 3271, CSA
Irradiated PVC <b>Temperature:</b> 80°C <b>Voltage:</b> 150 Volts UL and CSA Listed	26/07	Contact for Availability	UL 1429, CSA
	24/07		
	24/19	0, 2, 9	
	22/07	0, 2, 9	
	22/19	0	
	20/19	9	
	18/07	Contact for Availability	
	18/19	9	
	16/19	Contact for Availability	
	14/19		
12/19			
Irradiated PVC <b>Temperature:</b> 105°C <b>Voltage:</b> 300 Volts UL and CSA Listed	24/07	Contact for Availability	UL 1430, CSA
	22/07	0, 9	
	22/19	0, 2, 9	
	20/07	Contact for Availability	
	20/19	0, 2, 5, 9	
	18/07	Contact for Availability	
	18/19	0, 2, 5, 9	
	16/19	0, 2, 9	
	14/19	Contact for Availability	
12/19			
Irradiated PVC <b>Temperature:</b> 105°C <b>Voltage:</b> 600 Volts UL and CSA Listed	26-4/0 Various Strandings	Contact for Availability	UL 1431, CSA