

S2HM250HIRHSH1



Article Number: 151-29403

Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHSUV, Black, 500/pkg



Download spec sheet

Base Data

Local Order Number S2HM250HIRHSH1

Type S2HM25

Color Black (BK)

Features and Benefits

- Separates bundles from wear and chafing, providing additional longevity.
- Hexagonal retention feature captures a bolt or nut requiring tool access from the back side only.
- Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.

Product Description HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc...) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, this "H" profile on the saddle mount provides a tight circumferential loop on large and small bundles.

Fixation Method (FF) Screw Mounting and Rivet

Short Description Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHSUV, Black, 500/pkg

Product Dimensions

Length L (Imperial) 1.8 "

Length L (Metric) 45.0 mm

Width W (Imperial) 1.2 "

Width W (Metric) 30.0 mm

Cable Tie Width Max. (Imperial) 0.53 "

Cable Tie Width Max. (Metric) 13.5 mm

Height H (Imperial) 0.9 "

Height H (Metric) 23.0 mm

Height H2 (Imperial) 0.6 "

Height H2 (Metric) 15.0 mm

Bundle Diameter Max. (Imperial) 3.5 "

Bundle Diameter Max. (Metric) 89.0 mm

Mounting Hole Diameter D (Imperial) 0.24 "

Mounting Hole Diameter D (Metric) 6.0 mm

Stud Size (Imperial) 0.25 "

Stud Size (Metric) 6.35 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 500

Weight (Metric) 9.88 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS compliant (Article 4 - 1) Yes