Plugs & connectors



Standard grade spring action thermoplastic plugs & connectors

Product description

2-pole, 2-wire non-grounding 15A, 125V/AC

Spring action plugs & connectors



1-15R

Design features

Rating

· Made of high impact-resistant thermoplastic for long-term durability

· Cord clips on equipped plugs provide easy storage on appliances such as vacuum cleaners and fans



SA940



SA155

Plug V/AC Description **Cord diameter Color suffix** catalog no. catalog no.

15	125	NEMA 1-15, straight body, polarized, with cord clip	0.33" (8.3mm)	W	□ SA940		•
15	125	NEMA 1-15, straight body, polarized, with cord clip	0.33" (8.3mm)	BK	□ SA940		•
15	125	NEMA 1-15, straight body, polarized	0.33" (8.3mm)	B, BK, GD, W	□ SA540	□ SA155	•
15	125	NEMA 1-15, straight body, polarized	0.33" (8.3mm)	ВК	□ SA540	□ SA155	•

cULus Listed to UL498, file no. E15012; CSA certified to C22.2, no. 42

Standard grade spring action thermoplastic plugs & connectors

Product description

2-pole, 2-wire grounding 15A, 125V/AC





Connector

5-15P

5-15R


Design features

• Made of high impact-resistant thermoplastic for long-term durability

· Plug blades firmly embedded in body



SA399



(II)	(1)	<u>NON</u> 426
------	------------	-------------------

Ra	ating				Plug	Connector	∞
Α	V/AC	Description	Cord diameter	Color suffix	catalog no.	catalog no.	_
15	125	NEMA 5-15, straight body	0.33" (8.3mm)	BK	□ SA399	□ SA993	•

Listed to UL498, file no. E15012; CSA certified to CSA C22.2, no. 42; SA933 also NOM certified



SA993

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), BK (Black), GD (Translucent Gold), W (White).



Dimensional information: B-71 Specification information: Please visit www.cooperwiringdevices.com Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page F-21