



Harbour
INDUSTRIES
High Performance Wire & Cable

SAE AS 22759 REFERENCE GUIDE

Style	AWG sizes	Conductor	Voltage	Temp °C	WC27500	Dielectric material
22759/5	24-4	SPC	600	200°	VA	Extruded Mineral filled PTFE
22759/6	24-4	NPC	600	260°	WA	Extruded Mineral filled PTFE
22759/7	24-4	SPC	600	200°	SA	Extruded Mineral filled PTFE
22759/8	24-4	NPC	600	260°	TA	Extruded Mineral filled PTFE
22759/9	28-12	SPC	1000	200°	LE	Extruded PTFE
22759/10	28-12	NPC	1000	260°	LH	Extruded PTFE
22759/11	28-8	SPC	600	200°	RC	Extruded PTFE
22759/12	28-8	NPC	600	260°	RE	Extruded PTFE
22759/20	28-20	SPA	1000	200°	TK	Extruded PTFE
22759/21	28-20	NPA	1000	260°	TL	Extruded PTFE
22759/22	28-20	SPA	600	200°	TM	Extruded PTFE
22759/23	28-20	NPA	600	260°	TN	Extruded PTFE
22759/16	24-2/0	TPC	600	150°	TE	Extruded ETFE
22759/17	26-20	SPA	600	150°	TF	Extruded ETFE
22759/18	26-10	TPC	600	150°	TG	Extruded ETFE
22759/19	26-20	SPA	600	150°	TH	Extruded ETFE

***Above constructions are those currently
manufactured by Harbour Industries**