

37-119 • Single Conductor Portable Power Cable • DLO

Part No. 37-119-	Size AWG/kcmil	Minimum Wires per Conductor	Nominal Insulation Thickness in.	Nominal Jacket Thickness in.	Nominal Outside Diameter in.	Approx. Weight lbs. per 1,000 ft.	* Ampacity 90°C
201	14	19	0.045	0.015	0.214	31	35
202	12	19	0.045	0.015	0.233	41	40
203	10	37	0.045	0.015	0.257	58	55
204	8	168	0.055	0.030	0.349	77	80
205	6	61	0.055	0.030	0.365	124	105
207	4	133	0.055	0.030	0.460	203	140
209	2	259	0.055	0.030	0.534	265	190
210	1	224	0.065	0.045	0.623	415	220
211	1/0	266	0.065	0.045	0.668	489	260
212	2/0	323	0.065	0.045	0.689	562	300
213	3/0	418	0.065	0.045	0.771	757	350
214	4/0	532	0.065	0.045	0.822	894	405
215	262	646	0.075	0.065	0.957	1091	467
216	313	777	0.075	0.065	1.008	1245	522
217	373	925	0.075	0.065	1.074	1486	591
218	444	1110	0.075	0.065	1.143	1749	652
219	535	1332	0.090	0.065	1.257	2099	728
220	646	1591	0.090	0.065	1.361	2464	815
221	777	1924	0.090	0.065	1.439	2899	904
222	929	2318	0.090	0.065	1.685	3501	1005
223	1111	2745	0.130	0.065	1.850	4166	1119

* **Ampacity** – Calculated with at 90°C conductor temperature and 30°C ambient air, per 2008 NEC, Table 310.17

• Cable diameters are subject to +/-5% manufacturing tolerance



SAVE TIME

**Order Your DLO Cable with
Factory Installed
Connectors**

SAVE MONEY

