

BOSTRIG™ TYPE P CONTROL CABLE 600V OR 0.6/1kV

Multi-conductor / unarmored

TYPE P CONTROL CABLE 600V or 0.6/1kV 12 & 10 AWG

A brand of the

Prysmian
Group

12 AWG • 3.08 mm²

Type Designation	Draka Number	Cable Diameter (nominal)		GLAND SELECTION			GLAND REFERENCE CHART	
				Explosion Proof: Unarmored	Non-Explosion Proof: Unarmored	Non-Explosion Proof: Unarmored	Explosion Proof: (Unarmored) Hub Size Reference	Non-Explosion Proof: (Unarmored) - NPT Thread Size Reference
C12PN-2	026224	0.430	10.9	424UB-02	494AB-52/ 53	494NE-04/ 05/ 08	01 = 1/2"	03 = 1/2" - 14 NPT
C12PN-3	026225	0.450	11.4	424UB-02	494AB-52/ 53	494NE-04/ 05/ 08	02 = 1/2"	04 = 1/2" - 14 NPT
C12PN-4	026226	0.490	12.4	424UB-02	494AB-53/ 55	494NE-05/ 08/ 10/ 14	03 = 3/4"	05 = 1/2" - 14 NPT
C12PN-5	026227	0.540	13.7	424UB-02/ 03	494AB-53/ 55	494NE-05/ 08/ 10/ 14	04 = 1"	08 = 3/4" - 14 NPT
C12PN-6	026228	0.580	14.7	424UB-02/ 03	494AB-53/ 55	494NE-05/ 08/ 10/ 14	05 = 1-1/4"	10 = 3/4" - 14 NPT
C12PN-7	026229	0.580	14.7	424UB-02/ 03	494AB-53/ 55	494NE-05/ 08/ 10/ 14	15 = 1-1/2"	14 = 1" - 11-1/2 NPT
C12PN-8	026230	0.620	15.7	424UB-03	494AB-53/ 55	494NE-05/ 08/ 10/ 14	06 = 2"	15 = 1" - 11-1/2 NPT
C12PN-10	026231	0.740	18.8	424UB-03/ 04	494AB-55/ 56	494NE-10/ 14/ 15/ 20	07 = 2-1/2"	20 = 1 1/4" - 11-1/2 NPT
C12PN-12	026232	0.760	19.3	424UB-04	494AB-55/ 56	494NE-10/ 14/ 15/ 20	08 = 3"	21 = 1 1/4" - 11-1/2 NPT
C12PN-16	026233	0.890	22.6	424UB-04	494AB-56	494NE-15/ 20	09 = 3-1/2"	27 = 1 1/2" - 11-1/2 NPT
C12PN-20	026234	0.970	24.6	424UB-04/ 05/ 15	494AB-56/ 57	494NE-15/ 20/ 21/ 27		32 = 2" - 11-1/2 NPT
C12PN-24	026235	1.080	27.4	424UB-05/ 15	494AB-57	494NE-21/ 27		38 = 2 1/2" - 8 NPT
C12PN-30	026236	1.150	29.2	424UB-05 /15/ 06	494AB-57	494NE-21/ 27		44 = 3" - 8 NPT
C12PN-37	026237	1.240	31.5	424UB-05/ 15/ 06	494AB-57/ 59	494NE-21/ 27/ 32		45 = 3" - 8 NPT
C12PN-44	026238	1.400	35.6	424UB-06	494AB-59	494NE-32		
C12PN-60	026239	1.550	39.4	424UB-06	494AB-59	494NE-32		
C12PN-91	026240	1.920	48.8	424UB-07	494AB-61	494NE-38		

10 AWG • 5.53 mm²

Type Designation	Draka Number	Cable Diameter (nominal)		GLAND SELECTION		
				Explosion Proof: Unarmored	Non-Explosion Proof: Unarmored	Non-Explosion Proof: Unarmored
C10PN-2	026241	0.490	12.4	424UB-02	494AB-53/ 55	494NE-05/ 08/ 10/ 14
C10PN-3	026242	0.510	13.0	424UB-02	494AB-53/ 55	494NE-05/ 08/ 10/ 14
C10PN-4	026243	0.560	14.2	424UB-02/ 03	494AB-53/ 55	494NE-05/ 08/ 10/ 14
C10PN-5	026244	0.620	15.7	424UB-03	494AB-53/ 55	494NE-05/ 08/ 10/ 14
C10PN-6	026245	0.680	17.3	424UB-03/ 04	494AB-55	494NE-10/ 14
C10PN-7	026246	0.680	17.3	424UB-03/ 04	494AB-55	494NE-10/ 14
C10PN-8	026247	0.730	18.5	424UB-03/ 04	494AB-55	494NE-10/ 14
C10PN-10	026248	0.900	22.9	424UB-04	494AB-56	494NE-15/ 20