

BOSTRIG™ TYPE P CONTROL CABLE 600V OR 0.6/1kV

Multi-conductor / unarmored

TYPE P CONTROL CABLE 600V or 0.6/1kV 12 & 10 AWG

A brand of the

Prysmian
Group

12 AWG • 3.08 mm²

| Type Designation | Draka Number | Cable Diameter (nominal) | | GLAND SELECTION | | | GLAND REFERENCE CHART | |
|------------------|--------------|--------------------------|------|----------------------------|--------------------------------|--------------------------------|---|--|
| | | in | mm | Explosion Proof: Unarmored | Non-Explosion Proof: Unarmored | Non-Explosion Proof: Unarmored | Explosion Proof: (Unarmored) Hub Size Reference | Non-Explosion Proof: (Unarmored) - NPT Thread Size Reference |
| | | | | | | | | |
| C12PN-2 | 026224 | 0.430 | 10.9 | 424UB-02 | 494AB-52/ 53 | 494NE-04/ 05/ 08 | 01 = 1/2" | 03 = 1/2" - 14 NPT |
| C12PN-3 | 026225 | 0.450 | 11.4 | 424UB-02 | 494AB-52/ 53 | 494NE-04/ 05/ 08 | 02 = 1/2" | 04 = 1/2" - 14 NPT |
| C12PN-4 | 026226 | 0.490 | 12.4 | 424UB-02 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 | 03 = 3/4" | 05 = 1/2" - 14 NPT |
| C12PN-5 | 026227 | 0.540 | 13.7 | 424UB-02/ 03 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 | 04 = 1" | 08 = 3/4" - 14 NPT |
| C12PN-6 | 026228 | 0.580 | 14.7 | 424UB-02/ 03 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 | 05 = 1-1/4" | 10 = 3/4" - 14 NPT |
| C12PN-7 | 026229 | 0.580 | 14.7 | 424UB-02/ 03 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 | 15 = 1-1/2" | 14 = 1" - 11-1/2 NPT |
| C12PN-8 | 026230 | 0.620 | 15.7 | 424UB-03 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 | 06 = 2" | 15 = 1" - 11-1/2 NPT |
| C12PN-10 | 026231 | 0.740 | 18.8 | 424UB-03/ 04 | 494AB-55/ 56 | 494NE-10/ 14/ 15/ 20 | 07 = 2-1/2" | 20 = 1 1/4" - 11-1/2 NPT |
| C12PN-12 | 026232 | 0.760 | 19.3 | 424UB-04 | 494AB-55/ 56 | 494NE-10/ 14/ 15/ 20 | 08 = 3" | 21 = 1 1/4" - 11-1/2 NPT |
| C12PN-16 | 026233 | 0.890 | 22.6 | 424UB-04 | 494AB-56 | 494NE-15/ 20 | 09 = 3-1/2" | 27 = 1 1/2" - 11-1/2 NPT |
| C12PN-20 | 026234 | 0.970 | 24.6 | 424UB-04/ 05/ 15 | 494AB-56/ 57 | 494NE-15/ 20/ 21/ 27 | | 32 = 2" - 11-1/2 NPT |
| C12PN-24 | 026235 | 1.080 | 27.4 | 424UB-05/ 15 | 494AB-57 | 494NE-21/ 27 | | 38 = 2 1/2" - 8 NPT |
| C12PN-30 | 026236 | 1.150 | 29.2 | 424UB-05 /15/ 06 | 494AB-57 | 494NE-21/ 27 | | 44 = 3" - 8 NPT |
| C12PN-37 | 026237 | 1.240 | 31.5 | 424UB-05/ 15/ 06 | 494AB-57/ 59 | 494NE-21/ 27/ 32 | | 45 = 3" - 8 NPT |
| C12PN-44 | 026238 | 1.400 | 35.6 | 424UB-06 | 494AB-59 | 494NE-32 | | |
| C12PN-60 | 026239 | 1.550 | 39.4 | 424UB-06 | 494AB-59 | 494NE-32 | | |
| C12PN-91 | 026240 | 1.920 | 48.8 | 424UB-07 | 494AB-61 | 494NE-38 | | |

10 AWG • 5.53 mm²

| Type Designation | Draka Number | Cable Diameter (nominal) | | GLAND SELECTION | | |
|------------------|--------------|--------------------------|------|----------------------------|--------------------------------|--------------------------------|
| | | in | mm | Explosion Proof: Unarmored | Non-Explosion Proof: Unarmored | Non-Explosion Proof: Unarmored |
| | | | | | | |
| C10PN-2 | 026241 | 0.490 | 12.4 | 424UB-02 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 |
| C10PN-3 | 026242 | 0.510 | 13.0 | 424UB-02 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 |
| C10PN-4 | 026243 | 0.560 | 14.2 | 424UB-02/ 03 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 |
| C10PN-5 | 026244 | 0.620 | 15.7 | 424UB-03 | 494AB-53/ 55 | 494NE-05/ 08/ 10/ 14 |
| C10PN-6 | 026245 | 0.680 | 17.3 | 424UB-03/ 04 | 494AB-55 | 494NE-10/ 14 |
| C10PN-7 | 026246 | 0.680 | 17.3 | 424UB-03/ 04 | 494AB-55 | 494NE-10/ 14 |
| C10PN-8 | 026247 | 0.730 | 18.5 | 424UB-03/ 04 | 494AB-55 | 494NE-10/ 14 |
| C10PN-10 | 026248 | 0.900 | 22.9 | 424UB-04 | 494AB-56 | 494NE-15/ 20 |