

37-401 • Single Conductor Portable Power Cable • Type W

Part No. 37-401-	Size AWG/kcmil	Minimum Wires per Conductor	Nominal Insulation Thickness in.	Nominal Jacket Thickness in.	Nominal Outside Diameter in.	Approx. Weight lbs. per 1,000 ft.	* Ampacity 90°C
008	8	133	0.060	0.075	0.460	136	80
006	6	133	0.060	0.095	0.550	202	105
004	4	133	0.060	0.095	0.600	268	140
003	3	133	0.060	0.095	0.620	318	165
002	2	259	0.060	0.095	0.690	375	190
001	1	259	0.080	0.095	0.760	479	220
010	1/0	266	0.080	0.095	0.810	555	260
020	2/0	323	0.080	0.095	0.832	675	300
030	3/0	418	0.080	0.095	0.900	794	350
040	4/0	532	0.080	0.095	0.960	959	405
250	250	627	0.095	0.095	1.070	1268	455
300	300	741	0.095	0.095	1.100	1315	505
350	350	888	0.095	0.095	1.160	1517	570
400	400	999	0.095	0.095	1.190	1681	615
500	500	1221	0.095	0.095	1.310	2039	700

* Ampacity is calculated with a 90°C conductor temperature and 30°C ambient air, per 2008 NEC, Table 400.5(B)

• Cable diameters and weights are subject to +/- 5% manufacturing tolerance

SAVE TIME

Order Your Type W Cable with
**Factory Installed
Connectors**



SAVE MONEY