

BOSTRIG™ TYPE P SIGNAL CABLE 600V

Overall shielded multiconductor / armored and sheathed
TYPE P SIGNAL CABLE 600V, 20, 18 & 16 AWG

A brand of the

Prysmian
Group

20 AWG • 0.61 mm²

Type Designation	Draka Number	Number of Conductors	Stranding	Insulation Thickness		Sheath Thickness		Cable Diameter (nominal)		Cable Weight (approximate)	
				in	mm	in	mm	in	mm	Lbs/Mft	Kg/Km
C(OS)20PNBS-3	T26503	3	19/32	.030	0.76	0.060	1.5	0.530	13.5	185	275
C(OS)20PNBS-4	T26504	4	19/32	.030	0.76	0.060	1.5	0.560	14.2	210	315
C(OS)20PNBS-5	T26505	5	19/32	.030	0.76	0.060	1.5	0.590	15.0	230	340
C(OS)20PNBS-6	T26506	6	19/32	.030	0.76	0.060	1.5	0.610	15.5	255	380

18 AWG • 0.96 mm²

Type Designation	Draka Number	Number of Conductors	Stranding	Insulation Thickness		Sheath Thickness		Cable Diameter (nominal)		Cable Weight (approximate)	
				in	mm	in	mm	in	mm	Lbs/Mft	Kg/Km
C(OS)18PNBS-3	T26507	3	19/30	.030	0.76	0.060	1.5	0.540	13.7	205	305
C(OS)18PNBS-4	T26508	4	19/30	.030	0.76	0.060	1.5	0.570	14.5	230	340
C(OS)18PNBS-5	T26509	5	19/30	.030	0.76	0.060	1.5	0.620	15.7	260	385
C(OS)18PNBS-6	T26510	6	19/30	.030	0.76	0.060	1.5	0.630	16.0	286	425
C(OS)18PNBS-25	-----	25	19/30	.030	0.76	0.080	2.0	1.110	28.2	705	1050

16 AWG • 1.23 mm²

Type Designation	Draka Number	Number of Conductors	Stranding	Insulation Thickness		Sheath Thickness		Cable Diameter (nominal)		Cable Weight (approximate)	
				in	mm	in	mm	in	mm	Lbs/Mft	Kg/Km
C(OS)16PNBS-3	T26511	3	19/29	.030	0.76	0.060	1.5	0.570	14.5	220	325
C(OS)16PNBS-4	T26512	4	19/29	.030	0.76	0.060	1.5	0.600	15.2	255	380
C(OS)16PNBS-5	T26513	5	19/29	.030	0.76	0.060	1.5	0.640	16.3	285	425
C(OS)16PNBS-6	T26514	6	19/29	.030	0.76	0.060	1.5	0.670	17.0	315	470
C(OS)16PNBS-12	-----	12	19/29	.030	0.76	0.060	1.5	0.820	20.8	470	700

This information is provided for reference only. Please consult the factory or your representative to confirm all engineering information.
This information is not intended to replace the information in the appropriate and applicable standard or code.