



1/0 AWG 1/C 8kV 100% MARINE

CONDUCTOR:	1/0 AWG 266W ROPE BUNCHED TINNED COPPER,	<u>TYPICAL</u> OD: 0.409"
CONDUCTOR SHIELD:	SEMI-CONDUCTING TAPE, HELICALLY APPLIED AND LAPPED, AND APPX 15 MILS OF EXTRUDED SEMI-CONDUCTING THERMOSETTING COMPOUND.	OD: 0.456
INSULATION:	115 MILS (MIN. AVG.) OF ETHYLENE PROPYLENE RUBBER (EPR).	OD: 0.693"
INSULATION SHIELD:	24 MILS (MIN. PT.) OF EXTRUDED SEMI-CONDUCTING THERMOSETTING COMPOUND AND A SEMI-CONDUCTING TAPE, HELICALLY APPLIED AND LAPPED	OD: 0.752"
BRAID SHIELD:	COMPOSITE BRAID OF .0126" TINNED COPPER WIRES AND COLORED NYLON YARN PROVIDING A MINIMUM OF 60% COPPER COVERAGE.	OD: 0.792"
SEPARATOR:	POLYESTER TAPE, HELICALLY APPLIED AND LAPPED.	
JACKET:	80 MILS (MIN. AVG.) OF BLACK HEAVY DUTY CHLORINATED POLYETHYLENE (CPE).	OD: 0.965"
VOLTAGE RATING:	8000 VOLTS	
APPX WEIGHT:	681 POUNDS PER 1000 FEET.	

AmerCable El Dorado, Arkansas THIS DRAWING AND SET OF PLANS, AND ALL INFORMATION AND SPECIFICATIONS SET FORTH HEREON, IS THE COPYRIGHTED AND CONFIDENTIAL EXCLUSIVE PROPERTY OF AMERCABLE INCORPORATED. ANY USE FOR ANY PURPOSE WHATSOEVER, INCLUDING WITHOUT LIMITATION COPYING OR DISTRIBUTION, WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMERCABLE INCORPORATED IS EXPRESSLY PROHIBITED. THIS DRAWING MUST BE RETURNED ON DEMAND BY AMERCABLE INCORPORATED.	REV	DATE	CHANGE	DRAWN BY	DATE
				Tim Ayant	01/30/12
	DIMENSIONAL TOLERANCE	SCALE	ENGINEERING APPROVAL	DATE	
	+/- 5%	NTS	Michael Hammons	01/30/12	
DRAWING NUMBER	REV	CUSTOMER APPROVAL	DATE		
37105122X	0	<i>[Signature]</i>			