Southwire WE DELIVER POWER ... RESPONSIBLY*

PRODUCT DATA SHEET

(10)

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 30009

DESCRIPTION: 14/4 & 16/8 STRANDED AWM 20904 SEOW FLEXIBLE POWER CABLE

CONSTRUCTION: This cable consists of four 14ga and eight 16ga bare copper insulated conductors cabled with fillers and an overall jacket.

APPLICATION: UL Subject 62 & 758 Style 20904

APPROVALS: 600V Portable Oil and Water Resistant Outdoor Flexible Power Cable

Construction Parameters:

Conductor 14 AWG Bare Copper 16 AWG Bare Copper

14ga: 41/30

 Stranding
 14ga: 41/30

 16ga: 26/30

 Insulation Material
 PVC

 Insulation Thickness
 14ga: 0.046" Nom.

 16ga: 0.031" Nom.

 Insulated Conductor Diameter
 14ga: 0.166" Nom.

 16ga: 0.121" Nom.

Number of Conductors 14ga: 4 16ga: 8

 Lay Length
 7.75" Nom.

 Filler Type
 Polypropylene

 Separator/Wrap
 Paper Tissue

 Jacket Material
 PVC

 Jacket Thickness
 0.107" Nom.

 Overall Cable Diameter
 0.775" Nom.

Approximate Cable Weight 362.5 Lbs/1M' Nom.

Flame Rating UL/CSA Horizontal Flame Test

Electrical Properties:

Temperature Rating -40°C to 105°C
Operating Voltage 600 V RMS Max.
DC Resistance per 12 AWG Conductor @ 20°C 2.53 Ohms/1M' Nom.
DC Resistance per 18 AWG Conductor @ 20°C 4.95 Ohms/1M' Nom.

Insulation Colors 14 AWG: 5. Green 6. White 7. Red 8. Black

16 AWG: 1. Green 2. Green 3. Orange 4. Blue 9. White/Black 10. Blue/Black

11. Orange/Black 12. Red/Black

Jacket Color Black

Legend (White Surface Ink Print) E46194 (UL) 14-4 & 16-8 SEOW AWM 20904 105C(-40C)

This product complies with European Directive 2011/65/EU (RoHS-2)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwiree's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Customer Name
Customer Approval
Specification Issue Date: July 16, 2015