			DATE	REV	ECN	DESCRIPTION
<u>PRODUCT</u>	<u>SPECIFICATION</u>		10/24/2013	А	E26449	SPECIFICATION CREATED
Parent Number:	F24054-	DIAMETER: (0.056 -			
Description:	24 7/.0076 TC AWM 3068 SEWF-1 Braided	TOLERANCE ± : 9				<u> </u>
-	<u>Silicone</u> 7/.0076 TC LHL UL: AWM 3068 CSA: SEWF-1	<i>IOLERANCE</i> ± : <u>0</u>	<u>0.003</u>	V		IN AVERAGE WALL: 0.015 MINIMUM WALL: 0.013
Insulation:	Braided Silicone					
<u>Print Legend:</u>	24 AWG (.205mm2) E96824 (PLANT ID CODE) (AWM LO	GO) AWM 3068 150C 3	300V 15601	<u>6 CSA SE</u>	WF-1 150	<u>C 300V</u>
<u>Voltage:</u>	<u>300V</u>					
<u>Temperature:</u>	<u>150C</u>					
<u>Notes:</u>	 Diameter shown is OD under braid. The OD over the braid is approximately 0.061". 					
The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.						
This specification is pr without written conser	roprietary intellectual property of Coleman Cable. Any information on to f Coleman Cable.	contained herein shall not b	e disclosed to	any party	COI	LEMAN CABLE, INC
Customer Appro						tields Drive
	* Nbr(s):				J	an, IL 60085
	Date:					1-800-323-9355
Title:_	Company	IName:			www.col	emancable.com