


PRODUCT SPECIFICATION

DATE	REV	ECN	DESCRIPTION
7/11/2008	A	13451	SPECIFICATION CREATED

Parent Number: F02087-

Description: 2 7x37/26 BC SGR ESF-M1L64-A Adhesive Separator

DIAMETER: 0.440
TOLERANCE ±: 0.010



Stranding: 7x37/26 BC Rope Lay

Style: SGR per SAE J1127, Ford ESF-M1L64-A

NOM WALL: 0.055
MINIMUM WALL: 0.045

Insulation: Synthetic Rubber

Print Legend: NO PRINT

Voltage: Per SAE J 1127 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems.

Temperature: The Temperature Class Rating is 80C. The Temperature Class rating is defined by SAE as " a class designation based on the retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Notes: 1. Separator is used between the copper conductor and insulation.

This product complies with European Directive 2002/95/EC (RoHS)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Approval:

Customer Part Nbr(s):

Approved By: John Stephens **Date:** 7-11-2012

Title: SEM - AM **Company Name:** IEWG

COLEMAN CABLE, INC
1530 Shields Drive
Waukegan, IL 60085
Phone: 1-800-323-9355
www.colemancable.com