PRODUCT SPECIFICATION

| DATE | REV | ECN | DESCRIPTION |
|----------|-----|------------|-----------------------|
| 1/8/2009 | Α | 21000 | SPECIFICATION CREATED |


Parent Number: 2 SGR 105C PRINTED

Description: 2 7x92/30 BC SGR per SAE J1127 EST-

M1L118-A 105C Printed

DIAMETER: 0.420

TOLERANCE ± : 0.008



Stranding: 7x92/30 BC Unilay

Style: SGR per J1127; Ford EST-M1L118-A

Insulation: EPDM

Print Legend: 2 GA SAE J1127 TYPE SGR 105C

Voltage: Per SAE J 1127 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical

systems.

Temperature: The Temperature Class Rating is 105C. The Temperature Class rating is defined by SAE as " a class designation based on the

retention of mechanical properties after 168 hours of aging at 30C above the temperature class rating".

Notes: 1. Temporary part number only - permanent part number to be assigned upon order.

| This product complies w | rith European Directive 2002/95/EC (RoHS) | |
|-------------------------|---|--|
| Customer Approval: | | |
| Customer Part Nbr(s): | | |
| Approved By: | | |
| Title: | Company Name: | |
| | | |

COLEMAN CABLE, INC

1530 Shields Drive Waukegan, IL 60085

CCI

Phone: 1-800-323-9355 www.colemancable.com