

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Product Specification

Customer: IEWC

TOL Part Number: SGR-6-1003

Description: 6 GA EPDM INSULATED RUBBER BATTERY CABLE,
80DEGC, 133 STRANDS BARE COPPER

Conductor (Stranding): 7 x 19 x .0136" Bare Copper , Auto

Conductor OD (Nom) 0.210 inches

Max. Lay Length: 3.0 inch Lay

Nom. Wall Thickness: 0.060 inches

Max O.D: 0.340 inches

Min O. D: 0.294 inches

Max Runout: 0.012 inches

Paper Separator: One 3/4" paper

Circular Mils (CMA): 23879 (Min)

Surface Print: None

Specification Reference Data

SAE: J-1127	Ford: MIL 34-A	Chrysler: N/A
UL : N/A	CSA: N/A	Packard: N/A Other: N/A

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Quality Engineer)

Date: 3-3-2014
Mat'l Spec Form (#F-0270)

Rev. 0

7-30-1998