

# PRODUCT SPECIFICATION


DATE	REV	ECN	DESCRIPTION
6/25/2013	A	E25356	SPECIFICATION CREATED

Parent Number:

Description: 2/0 19x70/30 BC SGR per J1127 120C  
Print

DIAMETER: 0.622

TOLERANCE ±: 0.015



Stranding: 19x70/30 BC Unilay

NOM WALL: 0.101

Style: SGR per SAE J1127

MINIMUM WALL: 0.065

Insulation: EPDM

Voltage: Per SAE J 1127 & Daimler 48-25450 this product is intended for use at a nominal system voltage of 60 Volts DC or less in surface vehicle electrical systems.

Temperature: 120C ~40 C

Notes: 1. Separator is used between the conductor and insulation.

This product complies with European Directive 2011/65/EU (RoHS 2)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Approval:

Customer Part Nbr(s):

Approved By:

Date:

Title:

Company Name:

**COLEMAN CABLE, INC**

1530 Shields Drive  
Waukegan, IL 60085

Phone: 1-800-323-9355

www.colemancable.com

