

TABLE OF CONTENTS

- A. GENERAL INFORMATION
- B. APPLIANCE WIRE
 - 1. Appliance Wire (PVC)
 - Machine Tool Wire, Dual Rated, UL-1015/1230/TEW
 - Lead Wire, UL-1007, UL-1028
 - UL-1056, UL-1060
 - 2. Appliance Lead Wire (XLPE)
 - UL-3173, 3915, 3196
 - UL-3199
 - UL-3237, 3290
 - UL-3321
 - 3. Appliance Lead Wire (Neoprene) NO LONGER AVAILABLE
UL-3039, 3044, 3046
 - 4. Appliance Lead Wire (EPDM) NO LONGER AVAILABLE
UL-3284, 3328, 3340, 3484, 3556
 - 5. Hermetic Lead Wire
 - UL-5170 (DMD)
 - UL-5058 (DTMD)
- C. AUTOMOTIVE WIRE & CABLE
 - 1. Automotive Primary Wire (PVC)
 - GPT (General Purpose Thermoplastic)
 - HDT, HTP (Heavy Duty Thermoplastic)
 - TWP (Thin Wall Thermoplastic)
 - UTP (Ultra-Thin Wall Thermoplastic)
 - 2. Automotive Primary Wire (XLPE)
 - GXL (General Purpose Crosslink)
 - SXL (Special Purpose Crosslink)
 - TXL (Thin Wall Crosslink)
 - UXL (Ultra-Thin Wall Crosslink)
 - 3. Automotive Battery Cable
 - SGT (PVC)
 - SGX (XLPE)
 - STX (Thin Wall XLPE)
- D. MARINE WIRE
 - Marine Wire (PVC)
 - Marine Battery Cable (SGT)
- E. CONSTRUCTION WIRE (XLPE)
 - XHHW, XHHF
 - RHH, USE, RHW
- F. SWITCHGEAR WIRE (XLPE)
 - SIS
 - SIS-F (VW-1 Rating)
- G. MULTI-CONDUCTOR CABLE (PVC Jacket)
 - Trailer Cable
 - Boat Cable



ORDERING INFORMATION

PART NUMBER

GXL - 16 - 19 - B - xx
 Product Type Gauge Stranding Coating Specialty Code

Product Type: Type as referenced on catalog page (GXL, TWP,3321, etc.)
 Gauge: Wire gauge (16, 1/0, etc.)
 Stranding: Number of strands (19, 133, etc.) or special number (1000, 1010, etc.)
 Coating: "B" for bare copper or "T" for tinned copper
 Specialty Code: See customer service for designation

PACKAGING

Reels: Wood, Non-returnable
 12R - 12" Reel
 15B - 15" X 10", 1-9/16" Arbor
 16B - 16" x 12"
 18A - 18" x 14", 2" Arbor
 18B - 18" x 14", 1-9/16" Arbor
 18C - 18" x 14", 2" Arbor, 3/4" Flange
 24R - 24" Reel, 2" Arbor
 30A - 30" x 14", 2" Arbor
 30B - 30" Reel, 1-1/2" Flange

Reels: Wood, Non-returnable
 30R - 30" x 14", 1-9/16" Arbor
 36A - 36" x 12", 2" Arbor
 36B - 36" x 14", 3" Arbor

Drums: Fiber, Non-returnable
 35D - 35 Gallon, 20" high x 23" diameter
 55D - 55 Gallon, 30" high x 23" diameter
 75D - 75 Gallon, 42" high x 23" diameter

ACCEPTANCE OF ORDERS:

All orders are subject to written acceptance by Therm-O-Link, Inc. / Vulkor, Inc.

CREDIT:

All orders are subject to credit approval.

PRICING:

Material will be invoiced at the price in effect at the time of shipment.

TERMS OF PAYMENT:

Net 30 days cash.

FREIGHT TERMS:

Prices are FOB factory, shipped collect, unless otherwise stated.

QUANTITY VARIATION:

The quantity shipped against any item on an order is subject to a variation of +/- 10%.

WARRANTY:

Therm-O-Link, Inc. / Vulkor, Inc. warrants that the wire furnished is free from defects in material and workmanship. There is no other warranty expressed or implied.

RETURN POLICY:

No material will be accepted for return without prior written authorization.

MARINE BATTERY CABLE

MARINE Revised Nov.2009

Polyvinyl chloride (PVC) insulated wire manufactured to SAE J1127 standards.

SGT (Printed) Bare Copper 105°C 60 Volts

| Product | #CU/MFT | Stranding | Wall Thickness | Min Order |
|--------------|---------|-----------|----------------|-----------|
| SGT-6-1002 | 82.00 | 133/0140 | .050 | 50M |
| SGT-2-1000 | 199.04 | 133/0217 | .065 | 5M |
| SGT-1-1000 | 241.24 | 133/0242 | .065 | 5M |
| SGT-1/0-1001 | 306.92 | 133/0273 | .065 | 5M |
| SGT-2/0-1001 | 387.79 | 133/0307 | .065 | 4M |
| SGT-3/0-1002 | 491.77 | 266/0244 | .078 | 3M |
| SGT-4/0-1004 | 652.00 | 418/0224 | .078 | 2.4M |

SGT (Non-Printed) Bare Copper 105°C 60 Volts

| Product | #CU/MFT | Stranding | Wall Thickness | Min Order |
|--------------|---------|-----------|----------------|-----------|
| SGT-1/0-1000 | 306.92 | 133/0273 | .065 | 5M |
| SGT-2/0-1000 | 387.79 | 133/0307 | .065 | 4M |

Minimum order requirement reflects quantity per color, per release.
Black and red quantities may be combined to determine pricing.

800-776-9223 (Ohio) 800-684-7823 (Texas)