

THERM-O-LINK INC.

P.O.BOX 285
GARRETTSVILLE, OHIO 44231-0285

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL spec ID : SGT-6-1010

Description: 6 GA SGT Cable PVC 105 DegC , 49 Strands Bare Copper

Conductor (Stranding): 49 x .0221" Bare Copper
Conductor OD (Nom) 0.180 inches
Max. Lay Length: 3.0 inch Lay
Nom. Wall Thickness: 0.060 inches
Min Wall Thickness: 0.054 inches
Max . O.D. 0.342 inches
Min O. D: 0.288 inches
Paper Serve : One 3/4" Paper
Max Runout: 0.012 inches
Circular Mils (CMA): 24538 (Min)
Surface Print: M M SGT 6 GA MARINE WIRE SAE J378 & J1127 60V
DC 105C

Specification Reference Data

SAE: J-1127	Ford: N/A	Chrysler: N/A
UL : N/A	CSA: N/A	Packard: N/A
Other: N/A		

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Date: 10-1-2012 By: Mir Hussain Title: Corporate Quality Engineer