


Product Catalog

For Web Assistance: (800) 323-0198



Company Profile and History



Product Quote Form



Find a Distributor



Contact Us

Product Index



- Hookup Wire
- Braided Stranded Copper Wire
- Multiconductor
- Tubing
- Coaxial Cable

Check the Items You'd Like to Add to Your Quote or Order

Premier Marine Wire and Cable

PREMIER BATTERY MARINE CABLE

<p>Standard Putups:</p> <ul style="list-style-type: none"> ● 100 ft. ● 500 ft. ● 1000 ft. <p>See color chart 8 in Technical Section. Consult factory for availability of other colors and color combinations.</p>	DESCRIPTION	FEATURES & APPLICATIONS																																																																																														
	<ul style="list-style-type: none"> ● Conductors: Extra-flexible corrosion-resistant tinned copper Type 3 marine stranding for longer life. ● Insulation: Elastoplex (TM), 105C insulation. 	<ul style="list-style-type: none"> ● For use in marine engine wiring assemblies as well as other electrical components. 																																																																																														
	CHARACTERISTICS	APPROVALS																																																																																														
	<ul style="list-style-type: none"> ● Temperature: 105C. ● Voltage Rating: 50 Volts DC, 600 Volts AC. ● Resistant To: Harsh marine environment, including salt water, oil, and gas. 	<ul style="list-style-type: none"> ● UL: Standard 1426 ● CSA: AWM I A/B and TEW. ● UL Listed Standard 1426 Boat Cable. SAE J1127 (8 AWG J1128), SAE J378. AWM Style 1283 & 1284. CSA AWM I A/B and CSA TEW. Type SGT. ABYC and Coast Guard requirements. Passes VW-1 Vertical Flame Test. 																																																																																														
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 5%;"></th> <th style="width: 15%;">Part Number</th> <th style="width: 10%;">AWG</th> <th style="width: 10%;">Stranding</th> <th style="width: 10%;">Nom. Insulation Thickness in. mm</th> <th style="width: 10%;">Nom. O.D. in. mm</th> <th style="width: 10%;">Approx. Ship WT./MFT.</th> <th style="width: 10%;">Color Code</th> </tr> </thead> <tbody> <tr><td><input type="checkbox"/></td><td>PBM0830</td><td>8</td><td>168/30</td><td>.060 1.52</td><td>.300 7.62</td><td>71.0</td><td>0,2,5,9</td></tr> <tr><td><input type="checkbox"/></td><td>PBM0630</td><td>6</td><td>266/30</td><td>.060 1.52</td><td>.344 8.73</td><td>109.0</td><td>0,2,5,9</td></tr> <tr><td><input type="checkbox"/></td><td>PBM0430</td><td>4</td><td>420/30</td><td>.065 1.65</td><td>.400 10.16</td><td>161.0</td><td>0,2</td></tr> <tr><td><input type="checkbox"/></td><td>PBM0230</td><td>2</td><td>665/30</td><td>.065 1.65</td><td>.469 11.91</td><td>254.0</td><td>0,2</td></tr> <tr><td><input type="checkbox"/></td><td>PBM0130</td><td>1</td><td>836/30</td><td>.080 2.03</td><td>.545 13.84</td><td>312.0</td><td>0,2</td></tr> </tbody> </table>		Part Number	AWG	Stranding	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Approx. Ship WT./MFT.	Color Code	<input type="checkbox"/>	PBM0830	8	168/30	.060 1.52	.300 7.62	71.0	0,2,5,9	<input type="checkbox"/>	PBM0630	6	266/30	.060 1.52	.344 8.73	109.0	0,2,5,9	<input type="checkbox"/>	PBM0430	4	420/30	.065 1.65	.400 10.16	161.0	0,2	<input type="checkbox"/>	PBM0230	2	665/30	.065 1.65	.469 11.91	254.0	0,2	<input type="checkbox"/>	PBM0130	1	836/30	.080 2.03	.545 13.84	312.0	0,2	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 5%;"></th> <th style="width: 15%;">Part Number</th> <th style="width: 10%;">AWG</th> <th style="width: 10%;">Stranding</th> <th style="width: 10%;">Nom. Insulation Thickness in. mm</th> <th style="width: 10%;">Nom. O.D. in. mm</th> <th style="width: 10%;">Approx. Ship WT./MFT.</th> <th style="width: 10%;">Color Code</th> </tr> </thead> <tbody> <tr><td><input type="checkbox"/></td><td>PBM0001</td><td>1/0</td><td>1064/30</td><td>.080 2.03</td><td>.593 15.06</td><td>383.0</td><td>0,2</td></tr> <tr><td><input type="checkbox"/></td><td>PBM0002</td><td>2/0</td><td>1323/30</td><td>.080 2.03</td><td>.652 16.56</td><td>464.0</td><td>0,2</td></tr> <tr><td><input type="checkbox"/></td><td>PBM0003</td><td>3/0</td><td>1666/30</td><td>.080 2.03</td><td>.703 17.85</td><td>612.0</td><td>0,2</td></tr> <tr><td><input type="checkbox"/></td><td>PBM0004</td><td>4/0</td><td>2107/30</td><td>.080 2.03</td><td>.758 19.25</td><td>765.0</td><td>0,2</td></tr> </tbody> </table>								Part Number	AWG	Stranding	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Approx. Ship WT./MFT.	Color Code	<input type="checkbox"/>	PBM0001	1/0	1064/30	.080 2.03	.593 15.06	383.0	0,2	<input type="checkbox"/>	PBM0002	2/0	1323/30	.080 2.03	.652 16.56	464.0	0,2	<input type="checkbox"/>	PBM0003	3/0	1666/30	.080 2.03	.703 17.85	612.0	0,2	<input type="checkbox"/>	PBM0004	4/0	2107/30	.080 2.03	.758 19.25	765.0	0,2
		Part Number	AWG	Stranding	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Approx. Ship WT./MFT.	Color Code																																																																																								
	<input type="checkbox"/>	PBM0830	8	168/30	.060 1.52	.300 7.62	71.0	0,2,5,9																																																																																								
	<input type="checkbox"/>	PBM0630	6	266/30	.060 1.52	.344 8.73	109.0	0,2,5,9																																																																																								
	<input type="checkbox"/>	PBM0430	4	420/30	.065 1.65	.400 10.16	161.0	0,2																																																																																								
	<input type="checkbox"/>	PBM0230	2	665/30	.065 1.65	.469 11.91	254.0	0,2																																																																																								
<input type="checkbox"/>	PBM0130	1	836/30	.080 2.03	.545 13.84	312.0	0,2																																																																																									
	Part Number	AWG	Stranding	Nom. Insulation Thickness in. mm	Nom. O.D. in. mm	Approx. Ship WT./MFT.	Color Code																																																																																									
<input type="checkbox"/>	PBM0001	1/0	1064/30	.080 2.03	.593 15.06	383.0	0,2																																																																																									
<input type="checkbox"/>	PBM0002	2/0	1323/30	.080 2.03	.652 16.56	464.0	0,2																																																																																									
<input type="checkbox"/>	PBM0003	3/0	1666/30	.080 2.03	.703 17.85	612.0	0,2																																																																																									
<input type="checkbox"/>	PBM0004	4/0	2107/30	.080 2.03	.758 19.25	765.0	0,2																																																																																									
ElastoPlex(TM) is a trademark of Dearborn/CDT.																																																																																																

If you wish to add the products to your quote or complete your quote check one of these buttons

[Add Items and Continue](#)

[Add Items and Generate Quote](#)

[Generate Quote](#)

[Home](#) | [Profile](#) | [Catalog](#) | [Quote Form](#) | [Representatives](#) | [Contact](#)

Copyright 1997-2001, Dearborn Wire and Cable, Inc.