1. CONDUCTOR:

1.1 Size and Material: 10 AWG, 19 strands, tin-plated copper wire.

1.2 O.D.: .113" nom.

2. INSULATION:

2.1 Extruded modified silicone rubber.

2.2 O.D.: .203" nom.

2.3 Marking on the insulation: as per UL and CSA Standards.

2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

2.5 Talc powder applied on the insulation.

3. PERFORMANCE:

3.1 Voltage rating: 600 VAC R.M.S.

3.2 Temperature rating: 200°C


4. REFERENCES:

4.1 UL Subject 758 (AWM), Style 3512.

4.2 CSA Standard C22.2 No.210 (AWM), Class I, Group A.

CUSTOMER APPROVAL

Sign:	 		
Date:			



UNCONTROLLED DOCUMENT
A later revision of this specification may exist.



This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

> MARMON H I I I

A member of The Marmon Group of companies

Date:

May 13, 2010

Verified: Dair War

Scale:

Size:

May 13, 2010

1 of 1



1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3
Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com

Description:

Code Ident. No:

57104

DURO 200 10 19/0234-X

Specification No.:
F04911-X

Rev.

Wire & Cable Specification - HBR.04.86.D