

1. CONDUCTOR:

- 1.1 Size and Material: 12 19/.0185" AWG tin-plated copper wire.
- 1.2 O.D.: .088" nom.

2. INSULATION:

- 2.1 Extruded modified silicone rubber.
- 2.2 O.D.: .148" nom.
- 2.3 Marking on the insulation: as per UL and CSA Standards.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.5 Talc powder applied on the insulation.

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C




4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 3512.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I, Group A.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								 This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.		Done: <i>Pierre Garand</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourfid.com							
										Date: January 8, 2007									
										Verified: <i>Carole</i>									
										Date: January 9, 2007		Description: DURO 200 12 19/0185-X							
										Size: A		Scale: ---		Page: 1 of 1		Code Ident. No: 57104		Specification No.: F04728-X	
UNCONTROLLED DOCUMENT A later revision of this specification may exist.								 A member of The Marmon Group of companies		Wire & Cable Specification - HBR.04.86.D									