

1. CONDUCTOR:

- 1.1 Size and Material: 16 7/0192" AWG tin-plated copper wire.
- 1.2 O.D.: .058" nom.

2. INSULATION:

- 2.1 Extruded modified silicone rubber.
- 2.2 O.D.: .118" nom.
- 2.3 Marking on the insulation: as per UL and CSA Standards.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.5 Talc powder applied on the insulation.

3. PERFORMANCE:

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 200°C




4. REFERENCE:

- 4.1 UL Subject 758 (AWM), Style 3512.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I, Group A.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.	 <p style="font-size: small;">This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.</p>	Done: <i>Pierre Garand</i>	 <p style="font-size: x-small;">1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourtd.com</p>		
		Date: November 9, 2005			
		Verified: <i>David Lott</i>	Description: DURO 200 16 7/0192-X		
		Date: November 9, 2005			
UNCONTROLLED DOCUMENT A later revision of this specification may exist.	 <p style="font-size: x-small;">A member of The Marmon Group of companies</p>	Size: A Scale: --- Page: 1 of 1	Code Ident. No: 57104	Specification No.: F04469-X	Rev. ---