## 1. CONDUCTOR:

1.1 Size and Material: 18 7/.0152" AWG tin-plated copper wire.

1.2 O.D.: .0456" nom.

## 2. INSULATION:

2.1 Extruded modified silicone rubber.

2.2 O.D.: .1056" nom.

2.3 Marking on the insulation: as per UL and CSA Standards.

2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).

2.5 Talc powder applied on the insulation.

### 3. PERFORMANCE:

3.1 Voltage rating: 600 VAC R.M.S.

3.2 Temperature rating: 200°C

3.3 Adhesion of insulation on conductor: 3 to 8 lbs on 3 inches.

# 4. REFERENCES:

4.1 UL Subject 758 (AWM), Style 3512.


4.2 CSA Standard C22.2 No.210 (AWM), Class I, Group A.

#### 5. NOTES:

5.1 Weight: 8.83 lbs/MFT nom.

# **CUSTOMER APPROVAL**

Sign: \_\_\_\_\_\_
Date:



A later revision of this specification may exist.

This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.

A member of The Marmon Group of companies

Date: November 13, 2008

Verified: Carrier Cotte

Date:

Size:

November 14, 2008

Harbour

1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourltd.com

Description:

DURO 200 18 7/0152-X

1 of 1 Code Ident. No: **57104** 

Specification No.: F04477-X

Rev.