



SILVYN® BW-M

SILVYN® BW-M is a special mounting bracket to be used with a SILVYN® LKI connector to provide the proper sealing protection.



All dimensions are in mm.



Technical Data


Material: Passivated stainless steel

Part Number	Thread Size	A (inches)	A (mm)	B (inches)	B (mm)	C (inches)	C (mm)	D (inches)	D (mm)	øE (inches)	øE (mm)	Standard Pack Size
SILVYN® BW-M: Metric Brackets												
55000531	M16 x 1.5	0.79	20.0	1.97	50.0	1.30	33.2	1.58	40.0	0.67	17.0	25
55000541	M20 x 1.5	0.79	20.0	1.97	50.0	1.50	38.0	1.58	40.0	0.83	21.0	25
55000551	M25 x 1.5	0.79	20.0	2.36	60.0	1.85	46.9	1.97	50.0	1.02	26.0	25
55000561	M32 x 1.5	0.79	20.0	2.76	70.0	2.24	56.9	2.36	60.0	1.30	33.0	25
55000571	M40 x 1.5	0.79	20.0	3.15	80.0	2.64	67.0	2.76	70.0	1.61	41.0	25
55000572	M50 x 1.5	0.79	20.0	3.54	90.0	3.08	78.4	3.15	80.0	2.01	51.0	25

SILVYN® USK/USK-M

Conduit Connectors for SILVYN® FD-PU & SILVYN® FPS Conduit

The SILVYN® USK is specially designed to lock in the conduit and prevent pullout and twists that can be encountered during continuous flexing applications. It is tension and vibration resistant, providing a high quality connection between the protective conduit and the machine. SILVYN® USK is for use with SILVYN® FPS and FD-PU conduits.



Approvals



Technical Data

Material: Polypropylene **Temperature Range:** -10°C to +110°C

Locknuts: SKINTOP® GMP-GL, page 544 **Color:** Gray

IP Protection: IP54

Part Number	Thread Size	Conduit Outer Diameter (inches)	Conduit Outer Diameter (mm)	Thread Length (inches)	Thread Length (mm)	SILVYN® FPS Conduit	SILVYN® FD-PU Conduit	Standard Pack Size
SILVYN® USK: PG Threads								
52005810	PG 7	0.394	10.0	0.394	10.0	61711550	64453662	50
52005820	PG 9	0.551	14.0	0.394	10.0	61711590	64453672	50
52005830	PG 11	0.669	17.0	0.394	10.0	61711630	64453682	50
52005840	PG 13	0.748	19.0	0.394	10.0	61711670	64453692	50
52005850	PG 16	0.827	21.0	0.433	11.0	61711710	64453702	50
52005860	PG 21	1.063	27.0	0.433	11.0	61711750	64453712	25
52005870	PG 29	1.417	36.0	0.472	12.0	61711790	64453721	25
52005880	PG 36	1.772	45.0	0.472	12.0	61711830	64453731	25
52005900	PG 48	2.205	56.0	0.591	15.0	61711910	64453751	10
SILVYN® USK-M: Metric Threads								
55501300	M10 x 1.5	0.394	10.0	0.394	10.0	61711550	64453662	50
55501310	M12 x 1.5	0.551	14.0	0.472	12.0	61711590	64453672	50
55501320	M16 x 1.5	0.669	17.0	0.472	12.0	61711630	64453682	50
55501330	M20 x 1.5	0.827	21.0	0.512	13.0	61711710	64453702	50
55501340	M25 x 1.5	1.063	27.0	0.512	13.0	61711750	64453712	25
55501350	M32 x 1.5	1.417	36.0	0.591	15.0	61711790	64453721	25
55501360	M40 x 1.5	1.772	45.0	0.591	15.0	61711830	64453731	25
55501370	M50 x 1.5	2.205	56.0	0.630	16.0	61711910	64453751	10

Photographs are not to scale and are not true representations of the products in question. For current information go to our website. If not otherwise specified, all values relating to the product are nominal values.