

SILVYN® EL

Flexible Reinforced Spiral PVC Conduit

Application Advantage

- Smooth inner walls allow cables to be pulled through easily
- Durable, long-lasting conduit is rugged yet flexible



SILVYN® EL is designed with a flexible PVC casing that has a rigid PVC spiral welded into the conduit, allowing it to be very flexible while maintaining its shape.

Approvals

Complete the Installation



SILVYN®
MPC
page 571



SILVYN®
MPC 90°
page 572

Technical Data

Material:	PVC sheath with rigid PVC spiral	Color:	Gray (RAL 7001) (black available upon request)
Temperature Range:	-20°C to +70°C	Approvals:	RoHS

Part Number	Outer Diameter		Inner Diameter		Bend Radius		Conduit Coil Put-Ups (ft)	Thread Size for Fittings	
	(in)	(mm)	(in)	(mm)	(in)	(mm)		PG	Metric
61747360	0.579	14.7	0.394	10.0	0.787	20.0	98	PG 9	M16 x 1.5
61747370	0.654	16.6	0.472	12.0	0.984	25.0	98	PG 11 / PG 13	M16 / M20 x 1.5
61747380	0.815	20.7	0.630	16.0	1.181	30.0	98	PG 13 / PG 16	M20 x 1.5
61747390	1.091	27.7	0.866	22.0	1.575	40.0	98	PG 29	M25 x 1.5
61747400	1.205	30.6	0.984	25.0	1.772	45.0	98	PG 29	M32 x 1.5
61747410	1.319	33.5	1.102	28.0	1.969	50.0	98	PG 29	M32 x 1.5
61747420	1.614	41.0	1.378	35.0	2.362	60.0	98	PG 36	M40 x 1.5
61747430	1.827	46.4	1.575	40.0	2.756	70.0	98	PG 48	M50 x 1.5
61747440	2.252	57.2	1.969	50.0	3.346	85.0	98	PG 48	M63 x 1.5